

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.23

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> PADL	<u>PROCEDURE NAME</u> VOR RWY 1	<u>ORIGINAL/AMENDMENT</u> 10	<u>CITY</u> DILLINGHAM	<u>STATE</u> AK		
<u>AIRPORT ELEVATION</u> 82	<u>TDZE</u> 82	<u>SUPERSEDED</u> VOR RWY 1	<u>ORIGINAL/AMENDMENT</u> 9D	<u>DATED</u> 01/03/2019	<u>MAG VAR</u> 15E	<u>EPOCH YEAR</u> 2010
<u>FACILITY</u> DLG	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 5 SEPTEMBER 2024	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
ENYUJ/10.00 DME CCW	IAF	ZOKUJ/10.00 DME	NOPT				10.00 DME ARC		3400
ODWUJ/10.00 DME CCW	IAF	ZOKUJ/10.00 DME	NOPT				10.00 DME ARC		3400
PEDUJ/10.00 DME CCW	IAF	ZOKUJ/10.00 DME	NOPT				10.00 DME ARC		3400
ZOKUJ/10.00 DME CCW		EMHUT/10.00 DME					10.00 DME ARC		1800
OCDIJ/10.00 DME CW	IAF	EMHUT/10.00 DME	NOPT				10.00 DME ARC		1800
UFTIV/10.00 DME CW	IAF	EMHUT/10.00 DME	NOPT				10.00 DME ARC		1800
QOPRI/10.00 DME CW	IAF	EMHUT/10.00 DME	NOPT				10.00 DME ARC		1800
EMHUT/10.00 DME	IF	DLG VOR/DME					010.33	10.00 (DLG R-190)	1100

MISSED APPROACH

MAP:

2.84 NM AFTER DLG VOR/DME OR AT DLG VOR/DME 2.84 DME

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 2000 DIRECT DLG VOR/DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2000.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT L SIDE OF COURSE 190.33 OUTBOUND 2000 FT WITHIN 10 MILES OF DLG VOR/DME (IAF)

2.

3. FAC: 010.33 FAF: DLG VOR/DME DIST FAF TO MAP: 2.84 DIST FAF TO THLD: 2.84

4. MIN ALT: DLG VOR/DME 1100

8. MSA FROM: DLG VOR/DME 035-215 1800, 215-035 4100



EQUIPMENT REQUIREMENTS NOTES:

NOTES:

CHART NOTE: CIRCLING NA E OF RWY 01-19.
CHART NOTE: RWY 01 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART NOTE: VDP NA WHEN USING MANOKOTAK ALTIMETER SETTING.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MANOKOTAK ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET.

ADDITIONAL FLIGHT DATA:

DLG VOR/DME TO RW01: 3.26/45
CHART DLG R-230 AT ZOKUJ.
CHART 2000 PRIOR TO DLG VOR/DME.
HOLD S, RT, 010.85 INBOUND.
CHART FAS OBST: 175 TREE 590041N/1583351W.
CHART 261 TOWER 590002N/1583235W.
CHART VDP AT 1.52 DME.
DISTANCE VDP TO THLD 1.32 NM.
CHART DLG R-293 AT ENYUJ.
CHART DLG R-260 AT ODWUJ.
CHART DLG R-246 AT PEDUJ.
CHART DLG R-044 AT OCDIJ.
CHART DLG R-090 AT UFTIV.
CHART DLG R-105 AT QOPRI.
CHART CIRCLING ICON.

MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-01	540	1	458	540	1	458	540	1 3/8	458	540	1 3/8	458			
CIRCLING	540	1	458	540	1	458	700	1 3/4	618	700	2	618			



