

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW07
IXADY (IAF)	GUKBE (NOPT) (FB)	158.77 / 5.00	4000	CLIMB TO 4000 DIRECT OYNEM AND HOLD.
IXFAQ (IAF)	GUKBE (NOPT) (FB)	338.85 / 5.00	4000	
GUKBE (IF/IAF)	EWUHY (FB)	068.81 / 6.10	3400	
				ADDITIONAL FLIGHT DATA: HOLD E, RT, 249.13 INBOUND. CHART FAS OBST: 1819 TREE 420920N/0791628W EWUHY TO RW07: 3.04/52.

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD W GUKBE, RT, 068.81 INBOUND, 4000 FT. IN LIEU OF PT (IAF)
- FAC: 068.88 FAF: EWUHY DIST FAF TO MAP: 5.04 THLD: 5.04
- MIN. ALT: GUKBE 4000, EWUHY 3400
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 10W

EPOCH YEAR: 2000

MINIMUMS															
TAKEOFF: <u> </u>	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2120	1	398	2120	1	398	2120	1	398	2120	1 1/4	398			
CIRCLING	2180	1	457	2180	1	457	2240	1 1/2	517	2280	2	557			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DUNKIRK ALTIMETER SETTING AND INCREASE ALL MDA 200 FEET; INCREASE LNAV CATS C AND D AND CIRCLING CATS C AND D VISIBILITY 1/2 MILE.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE JAMESTOWN, NY	ELEVATION: 1723 TOZE: 1722 AIRPORT NAME: CHAUTAUQUA COUNTY/JAMESTOWN	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 1 17 DEC 2009	SUP: AMDT: ORIG DATED 04/18/2002
-------------------------------------	--	------------------------------	---	--

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	339/30 CW 159/30 (NOPT)	GUKBE (IF/IAF) (FB)	4000
2.	159/30 CW 249/30	IXADY (IAF) (FB)	4000
3.	249/30 CW 339/30	IXFAQ (IAF) (FB)	4000

CITY AND STATE

JAMESTOWN, NY

ELEVATION: 1723 TDZE: 1722

AIRPORT NAME:

CHAUTAUQUA COUNTY/JAMESTOWN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 7, AMDT 1

17 DEC 2009

SUP:

AMDT: ORIG

DATED: 04/18/2002

CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP: _____
AMDT: ORIG
DATED: 04/19/2002

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet. MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	GUKBE	GUKBE	010		HF	R	FB		068.8(059T)	004.0	04000
	IXADY	IXADY	010	IAP	IF		FB				
	IXADY	GUKBE	020		TF		FB	1.0	158.8(149T)	005.0	04000
	IXFAQ	IXFAQ	010	IAP	IF		FB				
	IXFAQ	GUKBE	020		TF		FB	1.0	338.9(329T)	005.0	04000
		GUKBE	010	FACF	IF		FB				04000
		EWUHY	020	FAP	TF		FB	0.5	068.8(059T)	006.1	03400
		RW07	030	MAP	TF		FO	0.3	068.9(059T)	005.0	01773

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	OYNEM	040		DF		FO	1.0			04000
	OYNEM	050		HM	R	FO	2.0	249.1(239T)	004.0	04000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	EWUHY	N420617.20	W0792153.20	N4206.287	W07921.887
	GUKBE	N420307.75	W0792853.86	N4203.129	W07928.898
	IXADY	N420724.44	W0793222.64	N4207.407	W07932.377
	IXFAQ	N415850.95	W0792525.55	N4158.849	W07925.426
	OYNEM	N421542.51	W0790047.74	N4215.709	W07900.796
	RW07	N420853.36	W0791605.22	N4208.889	W07916.087

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW07	01721	52

CITY AND STATE
JAMESTOWN, NY

ELEVATION: 1723 TDZE: 1722
 AIRPORT NAME:
 CHAUTAUQUA COUNTY/JAMESTOWN

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 7, AMDT 1
 17 DEC 2009

SUP:	
AMDT:	ORIG
DATED:	04/18/2002

Quoted