

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW34						
RISNE (IF/IAF)		KAKME (FB)		345.02 / 5.00				2000		CLIMB TO 2100 DIRECT ISOPE AND HOLD.						
KAKME (FAF)		RW34 (MAP) (FO)		345.00 / 5.16												
RW34 (MAP)		720 MSL		345.00												
720 MSL		ISOPE (FO)						2100								
										ADDITIONAL FLIGHT DATA: HOLD N, RT, 164.96 INBOUND. CHART FAS OBST: 503 TOWER 304404N/0892936W KAKME TO RW34: 3.00/37.4. CHART CIRCLING ICON. CHART BOGALUSA AWOS-3PT.						
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD S RISNE, RT, 345.02 INBOUND, 2000 FT. IN LIEU OF PT (IAF)																
3. FAC: 345.00 FAF: KAKME _____ DIST FAF TO MAP: 5.16 THLD: 5.16																
4. MIN. ALT: RISNE 2000, KAKME 2000																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																
8. MSA FROM: _____										MAG VAR: 2W			EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X						
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
CIRCLING	880	1	560	1120	1	800	1120	2 1/4	800	1120	2 1/2	800				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE BOGALUSA ALTIMETER SETTING; WHEN NOT RECEIVED, USE HATTIESBURG ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET AND INCREASE CIRCLING CAT B/C/D VISIBILITY 1/4 MILE. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: PROCEDURE NA AT NIGHT.																
CITY AND STATE POPLARVILLE, MS				ELEVATION: 320 TDZE: AIRPORT NAME: POPLARVILLE-PEARL RIVER COUNTY				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, ORIG 10 DECEMBER 2015				SUP: AMDT: NONE DATED		

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	255/30 CW 075/30 (NOPT) 255/15 CW 075/15	255/15 CW 075/15 RISNE (IF/IAF) (FB)	2800 2000
2.	075/30 CW 255/30 075/15 CW 255/15	075/15 CW 255/15 RISNE (IF/IAF) (FO)	2800 2000

QUALITY
25
CHECKED

CITY AND STATE
POPLARVILLE, MS

ELEVATION: 320 TDZE:
AIRPORT NAME:
POPLARVILLE-PEARL RIVER COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-B, ORIG
10 DECEMBER 2015

SUP:
AMDT: **NONE**
DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - M13

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
RISNE	010	RISNE	HF	FO		345.0			R			AA 02000		EE A
	010	RISNE	IF	FB								AA 02000		E I
	020	KAKME	TF	FB	0.5	345.0						AA 02000		E F
	030	RW34	TF	FO	0.3	345.0		3.00				AT 00356		GY M
	040		CA	FB		345.0						AA 00720		M
	050	ISOPE	DF	FO								AA 02100		EY
	060	ISOPE	HM	FO		165.0		R				AA 02100		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
ISOPE	N305716.27	W0893350.95
KAKME	N304155.91	W0892824.55
RISNE	N303708.34	W0892642.93

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW34	N304652.75	W0893009.63	00319	

QUALITY
25
CHECKED

CITY AND STATE POPLARVILLE, MS	ELEVATION: 320	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-B, ORIG 10 DECEMBER 2015	SUP:
	AIRPORT NAME: POPLARVILLE-PEARL RIVER COUNTY				AMDT: NONE
					DATED: