



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CAT C AND D AND CIRCLING CAT C VISIBILITY 1/4 MILE.


CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING PORT LAVACA ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	042/30 CW 222/30 (NOPT)	NAPTE (IF/IAF) (FB)	2100
2.	222/30 CW 042/30	NAPTE (IF/IAF) (FO)	2600



CITY AND STATE  
PALACIOS, TX

ELEVATION: 14      THRE: 12  
AIRPORT NAME:  
PALACIOS MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 13, ORIG  
10 JANUARY 2013

SUP:  
AMDT: NONE  
DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0  
SBAS SERVICE PROVIDER IDENTIFIER 0  
AIRPORT IDENTIFIER KPSX  
RUNWAY RW13  
APPROACH PERFORMANCE DESIGNATOR 0  
ROUTE INDICATOR  
REFERENCE PATH DATA SELECTOR 0  
REFERENCE PATH IDENTIFIER (APPROACH ID) W13A  
LTP/FTP LATITUDE 284350.6070N  
LTP/FTP LONGITUDE 0961526.4650W  
LTP/FTP ELLIPSOIDAL HEIGHT -00231  
FPAP LATITUDE 284247.2200N  
FPAP LONGITUDE 0961415.0700W  
THRESHOLD CROSSING HEIGHT (TCH) 00040.0  
TCH UNITS SELECTOR (METERS OR FEET USED) F  
GLIDEPATH ANGLE (GPA) 03.00  
COURSE WIDTH AT THRESHOLD 106.75  
LENGTH OFFSET 1224  
HORIZONTAL ALERT LIMIT (HAL) 40.0  
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

70FE5F34

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4  
LTP ORTHOMETRIC HEIGHT +00037  
FPAP ORTHOMETRIC HEIGHT +00037

QUALITY  
9  
CHECKED

CITY AND STATE  
PALACIOS, TX

ELEVATION: 14 THRE: 12  
AIRPORT NAME:  
PALACIOS MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 13, ORIG  
10 JANUARY 2013

SUP:  
AMDT: NONE  
DATED:

## RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KPSXK4FR13	ANAPTE	010NAPTEK4EA0EE	AR	HF			13210040	+ 02100	18000			A JS	
SUSAP KPSXK4FR13	R	010NAPTEK4EA0E	I	IF				+ 02100	18000			A JS	
SUSAP KPSXK4FR13	R	020GUDFYK4EA1E	F	051TF			13210080	+ 01700				A JS	
SUSAP KPSXK4FR13	R	020GUDFYK4EA2WALPV			ALNAV/VNAV	ALNAV						JS	
SUSAP KPSXK4FR13	R	021FIGERK4EA0E	S	031TF			13220035	V 0058000593		-300		A JS	
SUSAP KPSXK4FR13	R	030RW13 K4PG0GY	M	031TF			13220017	00052		-300		A JS	
SUSAP KPSXK4FR13	R	040	0	M	CA		1322	+ 00500				A JS	
SUSAP KPSXK4FR13	R	050NAPTEK4EA0EY	R	DF				+ 02100				A JS	
SUSAP KPSXK4FR13	R	060NAPTEK4EA0EE	R	HM			13220040	+ 02100				A JS	

[illegible][illegible]

CITY AND STATE  
PALACIOS, TX

ELEVATION: 14                      THRE: 12  
AIRPORT NAME: PALACIOS MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  
**RNAV (GPS) RWY 13, ORIG**  
 10 JANUARY 2013

SUP:	
AMDT:	<b>NONE</b>
DATED:	

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	NAPTE	NAPTE	010	IAF	HF	R	FO		132.1(135.1T)	004.0	AA 02100	
		NAPTE	010	FACF	IF		FB				AA 02100	
		GUDFY	020	FAF	TF		FB	0.5	132.1(135.1T)	008.0	AA 01700	
		FIGER	021	SDF	TF		FB	0.3	132.2(135.2T)	003.5	AA 00580	GS 00593
		RW13	030	MAP	TF		FO	0.3	132.2(135.2T)	001.7	AT 00052	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		132.2(135.2T)		AA 00500	
	NAPTE	050		DF	R	FO				AA 02100	
	NAPTE	060		HM	R	FO		132.2(135.2T)	004.0	AA 02100	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	FIGER	N284503.17	W0961648.24	N2845.053	W09616.804
	GUDFY	N284731.41	W0961935.44	N2847.524	W09619.591
	NAPTE	N285312.53	W0962600.96	N2853.209	W09626.016
	RW13	N284350.61	W0961526.47	N2843.844	W09615.441

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW13	00012	40

QUALITY  
CHECKED

CITY AND STATE <b>PALACIOS, TX</b>	ELEVATION: 14	THRE: 12	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			<b>RNAV (GPS) RWY 13, ORIG</b>	AMDT: <b>NONE</b>
	<b>PALACIOS MUNI</b>	<b>RNAV</b>		<b>10 JANUARY 2013</b>	DATED: