

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.			
TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW35 CLIMB TO 3000 DIRECT WOPEG AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 172.98 INBOUND. FAS OBST: 1559 AAO 352436N/0980000W CHART TDZ ELEVATION 1418 HEBOG TO RW35: 3.04/40			
IRW VORTAC	YORUD (FB)	245.88 / 15.07	3100				
DATTA	ISOBE (FB)	033.18 / 10.93	3100				
ISOBE (IAF)	WUSEN (NOPT) (FB)	082.92 / 5.00	3100				
YORUD (IAF)	WUSEN (NOPT) (FB)	263.04 / 5.00	3100				
WUSEN (IF/IAF)	HEBOG (FB)	352.98 / 6.10	3000				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)							
2. HOLD S WUSEN, RT, 352.98 INBOUND, 3100 FT. IN LIEU OF PT (IAF)							
3. FAC: <u>352.98</u> FAF: <u>HEBOG</u> DIST FAF TO MAP: <u>4.78</u> THLD: <u>4.78</u>							
4. MIN. ALT: <u>WUSEN 3100, HEBOG 3000</u>							
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>							
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>							
7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR							
8. MSA FROM: <u>RW35 3800</u>							

MINIMUMS															
TAKEOFF:	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> X	SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @			
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1820	1	402	1820	1	402	1820	1 1/4	402		NA				
CIRCLING	1940	1	522	1940	1	522	1940	1 1/2	522		NA				

NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WILEY POST ALTIMETER SETTING AND SEE 8260-10															
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.															

CITY AND STATE	ELEVATION: 1418 TDZE: 1418	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
EL RENO, OK	AIRPORT NAME:		RNAV (GPS) RWY 35, ORIG	AMDT: NONE
	EL RENO REGIONAL		APR 10 2008	DATED



**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. -
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

INCREASE ALL MDA'S 60 FEET. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON IRW VORTAC AIRWAY
RADIALS 188 CW 292.

CITY AND STATE

EL RENO, OK

ELEVATION: 1418 TDZE: 1418

AIRPORT NAME:

EL RENO REGIONAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG

APR 10 2008

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. -
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

PAGE 4 OF 5 PAGES

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	DATTA	DATTA	010		IF		FB				
	DATTA	ISOBE	020	IAF	TF		FB	2.0	033.2(040T)	010.9	03100
	DATTA	WUSEN	030		TF		FB	1.0	082.9(090T)	005.0	03100
	IRW	IRW	010		IF		FB				
	IRW	YORUD	020	IAF	TF		FB	2.0	245.9(253T)	015.1	03100
	IRW	WUSEN	030		TF		FB	1.0	263.0(270T)	005.0	03100
	WUSEN	WUSEN	010		HF	R	FB		353.0(360T)	004.0	03100
		WUSEN	010	FACF	IF		FB				03100
		HEBOG	020	FAF	TF		FB	0.5	353.0(360T)	006.1	03000
		RW35	030	MAP	TF		FO	0.3	353.0(360T)	004.8	01458

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	WOPEG	040		DF		FO	1.0			03000
	WOPEG	050		HM	R	FO	2.0	173.0(180T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	IRW	N352130.95	W0973633.22	N3521.516	W09736.554
	DATTA	N350841.19	W0981458.78	N3508.687	W09814.980
	HEBOG	N352309.78	W0980015.46	N3523.163	W09800.258
	ISOBE	N351702.90	W0980621.74	N3517.048	W09806.362
	WOPEG	N353946.13	W0980015.88	N3539.769	W09800.265
	WUSEN	N351703.16	W0980015.30	N3517.053	W09800.255
	YORUD	N351703.11	W0975408.86	N3517.052	W09754.148
	RW35	N352756.98	W0980015.58	N3527.950	W09800.260

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	01418	40

CITY AND STATE
EL RENO, OK

ELEVATION: 1418 TDZE: 1418
 AIRPORT NAME:
 EL RENO REGIONAL

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 35, ORIG
 APR 10 2008

SUP:
 AMDT: NONE
 DATED: