

<b>RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
<b>TERMINAL ROUTES</b>				<b>MISSED APPROACH</b>								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	<b>LNAV: RW32</b>  <b>CLIMB TO 2000 DIRECT PUNAE THEN VIA 358.19 TRACK TO UTELE AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> HOLD NW, RT, 138.38 INBOUND. CHART FAS OBST: 129 TREE 264107N/0812329W UROLE TO RW32: 3.05/40 CHART SOUTHWEST FLORIDA INTL ASOS, 124.65.								
LBV VORTAC	TIRTE (FO)	160.08 / 16.02	2000									
FORTL (IAF)	TIRTE (NOPT) (FB)	020.73 / 17.15	2000									
WINCO (IAF)	TIRTE (NOPT) (FB)	307.46 / 18.75	2000									
TIRTE (IF/IAF)	UROLE (FB)	321.83 / 6.65	1900									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. <b>HOLD SE TIRTE, RT, 321.83 INBOUND, 2000 FT. IN LIEU OF PT (IAF)</b> 3. FAC: <u>321.79</u> FAF: <u>UROLE</u> DIST FAF TO MAP: <u>5.69</u> THLD: <u>5.69</u> 4. MIN. ALT: <b>TIRTE 2000, UROLE 1900</b> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: <b>34:1 IS NOT CLEAR</b> 8. MSA FROM: <b>RW32 2600</b>				MAG VAR: <b>5W</b> EPOCH YEAR: <b>2010</b>								
<b>MINIMUMS</b>												
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X							
CATEGORY =====>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
<b>LNAV MDA</b>	<b>480</b>	<b>1</b>	<b>460</b>	<b>480</b>	<b>1</b>	<b>460</b>	<b>480</b>	<b>1 1/4</b>	<b>460</b>	<b>480</b>	<b>1 1/2</b>	<b>460</b>
<b>CIRCLING</b>	<b>580</b>	<b>1</b>	<b>560</b>	<b>580</b>	<b>1</b>	<b>560</b>	<b>580</b>	<b>1 1/2</b>	<b>560</b>	<b>800</b>	<b>2 1/2</b>	<b>780</b>
<b>NOTES:</b> CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LBV VORTAC VIA AIRWAY RADIALS 112 CW 157. CHART NOTE: USE SOUTHWEST FLORIDA INTL ALTIMETER SETTING; WHEN NOT RECEIVED, USE PAGE FIELD <b>ALTIMETER SETTING AND INCREASE ALL MDAS 20 FEET.</b>												
CITY AND STATE		ELEVATION: 20 TDZE: 20		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
LA BELLE, FL		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 32, ORIG			AMDT: NONE			
		LA BELLE MUNI				FEB 14 2008			DATED			



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

RUNWAY 12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP X14 K7GRW32 0051253218 N26440804W081252296+0000 00020012940075

1 2 3 4 5 6 7 8 9 0 1 2 3  
MSA 12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP X14 K7SRW32 K7PG 0 25180026 M

CITY AND STATE  
LA BELLE, FL

ELEVATION: 20 TDZE: 20  
AIRPORT NAME:  
LA BELLE MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 32, ORIG  
FEB 14 2008

SUP:  
AMDT: NONE  
DATED:



**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	FORTL	FORTL	010	IAF	IF		FB				
	FORTL	TIRTE	020		TF		FB	1.0	020.7(016T)	017.2	02000
	LBV	LBV	010		IF		FO				
	LBV	TIRTE	020		TF		FB	2.0	160.1(155T)	016.0	02000
	LBV	TIRTE	030		HF	R	FB		321.8(317T)	004.0	02000
	WINCO	WINCO	010	IAF	IF		FB				
	WINCO	TIRTE	020		TF		FB	1.0	307.5(303T)	018.8	02000
		TIRTE	010	FACF	IF		FB				02000
		UROLE	020	FAF	TF		FB	0.5	321.8(317T)	006.7	01900
		RW32	030	MAP	TF		FO	0.3	321.8(317T)	005.7	00060

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	321.8(317T)		00420
	PUNAE	050		DF		FB	1.0			02000
	UTELE	060		TF		FO	1.0	358.2(353T)		02000
	UTELE	070		HM	R	FO	2.0	138.4(133T)	004.0	02000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	LBV	N264941.43	W0812329.17	N2649.691	W08123.486
	FORTL	N261833.77	W0812108.46	N2618.563	W08121.141
	PUNAE	N264851.91	W0813020.60	N2648.865	W08130.343
	TIRTE	N263506.90	W0811557.27	N2635.115	W08115.955
	UROLE	N263958.63	W0812101.98	N2639.977	W08121.033
	UTELE	N265620.28	W0813120.34	N2656.338	W08131.339
	WINCO	N262502.53	W0805818.54	N2625.042	W08058.309
	RW32	N264408.04	W0812522.96	N2644.134	W08125.383

RUNWAY DATA	THRESHOLD	ELEVATION	TCH
RWY			
RW32	00020		40

CITY AND STATE  
LA BELLE, FL

ELEVATION: 20 TDZE: 20  
 AIRPORT NAME:  
 LA BELLE MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
 RNAV (GPS) RWY 32, ORIG  
 FEB 14 2008

SUP:  
 AMDT: NONE  
 DATED:

