

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW35
VICUK (IAF)	ROGVE (NOPT) (FB)	083.80 / 5.00	2500	CLIMBING RIGHT TURN TO 2500 DIRECT ROGVE AND HOLD.
WUBUG (IAF)	ROGVE (NOPT) (FB)	264.08 / 5.00	2500	
ROGVE (IF/IAF)	OVIYI (FB)	353.94 / 5.10	1800	
				ADDITIONAL FLIGHT DATA: FAS OBST: 210 AAO 600919N/1620345W OVIYI TO RW35: 3.05/40

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD S ROGVE, RT, 353.94 INBOUND, 2500 FT. IN LIEU OF PT (IAF)
- FAC: 353.97 FAF: OVIYI DIST FAF TO MAP: 5.41 THLD: 5.41
- MIN. ALT: ROGVE 2500, OVIYI 1800
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 15E

EPOCH YEAR: 2005

MINIMUMS

TAKEOFF: <input checked="" type="checkbox"/> STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input checked="" type="checkbox"/>												
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	620	1	608	620	1	608		NA			NA				
CIRCLING	740	1	728	740	1	728		NA			NA				

NOTES:  
CHART NOTE: USE BETHEL ALTIMETER SETTING.  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART NOTE: PROCEDURE NA AT NIGHT.  
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CITY AND STATE  EEK, AK	ELEVATION: 12 TDZE: 12 AIRPORT NAME:  EEK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG JUN 05 2008	SUP: AMDT: NONE DATED
-------------------------------	--	------------------------------	--	-----------------------------

QUALITY  
6  
CHECKED

## US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## TAA

	FROM	TO	ALT
1.	264/30 CW 341/30 (NOPT)	264/20 CW 341/20	3000
	341/30 CW 084/30 (NOPT)	341/20 CW 084/20	2500
	264/20 CW 084/20	ROGVE (IF/IAF) (FB)	2500
2.	084/30 CW 174/30	VICUK (IAF) (FB)	2500
3.	174/30 CW 264/30	174/14 CW 264/14	4900
	174/14 CW 264/14	WUBUG (IAF) (FB)	2500

CITY AND STATE

EEK, AK

ELEVATION: 12 TDZE: 12

AIRPORT NAME:

EEK

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG

JUN 05 2008

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

CITY AND STATE  EEK, AK	ELEVATION: 12 AIRPORT NAME:  EEK	TDZE: 12	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 35, ORIG JUN 05 2008	SUP:
					AMDT: NONE
					DATED:

5  
Chen

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	ROGVE	ROGVE	010		HF	R	FB		353.9 (009T)	004.0	02500
	VICUK	VICUK	010	IAF	IF		FB				
	VICUK	ROGVE	020		TF		FB	1.0	083.8 (099T)	005.0	02500
	WUBUG	WUBUG	010	IAF	IF		FB				
	WUBUG	ROGVE	020		TF		FB	1.0	264.1 (279T)	005.0	02500
		ROGVE	010	FACF	IF		FB				02500
		OVIYI	020	FAF	TF		FB	0.5	353.9 (009T)	005.1	01800
		RW35	030	MAP	TF		FO	0.3	354.0 (009T)	005.4	00050

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	ROGVE	040		DF	R	FO	1.0			02500
	ROGVE	050		HM	R	FO	2.0	353.9 (009T)	004.0	02500

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	OVIYI	N600713.42	W1620424.49	N6007.224	W16204.408
	ROGVE	N600212.17	W1620559.49	N6002.203	W16205.992
	VICUK	N600258.30	W1621550.54	N6002.972	W16215.842
	WUBUG	N600125.31	W1615608.91	N6001.422	W16156.149
	RW35	N601233.42	W1620243.04	N6012.557	W16202.717

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00010	40

CITY AND STATE  
EEK, AK

ELEVATION: 12 TDZE: 12  
 AIRPORT NAME:  
 EEK

FACILITY IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
 RNAV (GPS) RWY 35, ORIG  
 JUN 05 2008

SUP:  
 AMDT: NONE  
 DATED:

5  
 CHECKED