

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW10					
PONOC (IAF)		JAVNE (NOPT) (FB)		186.84 / 5.00				3000		CLIMB TO 3000 DIRECT DEHY AND HOLD.					
FESEK (IAF)		JAVNE (NOPT) (FB)		006.84 / 5.00				3000							
JAVNE (IF/IAF)		TONSR (FB)		096.84 / 6.04				2800							
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 277.18 INBOUND. CHART FAS OBST: 1289 TREE 405257N/0815450W CHART 1481 TOWER 405353N/0815859W TONSR TO RW10: 3.04/40					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)															
2. HOLD W JAVNE, RT, 096.84 INBOUND, 3000 FT. IN LIEU OF PT (IAF)															
3. FAC: 096.93 FAF: TONSR _____ DIST FAF TO MAP: 5.10 THLD: 5.10															
4. MIN. ALT: JAVNE 3000, TONSR 2800, COPAK/2.20 NM TO RW10 1860															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR															
8. MSA FROM: _____															
MAG VAR: 7W EPOCH YEAR: 2000															
MINIMUMS															
TAKEOFF: _____ STANDARD _____ X _____ SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: NA _____ STANDARD @ _____															
CATEGORY =====>		A		B		C		D		E					
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LNAV MDA		1540	1	427	1540	1	427	1540	1 1/4	427	1540	1 1/2	427		
CIRCLING		1600	1	464	1600	1	464	1600	1 1/2	464	1700	2	564		
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AKRON-CANTON RGNL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.															
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.															
CITY AND STATE WOOSTER, OH		ELEVATION: 1136 TDZE: 1113 AIRPORT NAME: WAYNE COUNTY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, ORIG 17 DEC 2009				SUP: AMDT: NONE DATED					

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	007/30 CW 187/30 (NOPT)	JAVNE (IF/IAF) (FB)	3000
2.	187/30 CW 277/30	187/20 CW 277/20	3100
3.	187/20 CW 277/20	PONOC (IAF) (FB)	3000
4.	277/30 CW 007/30	FESEK (IAF) (FB)	3000

CITY AND STATE

WOOSTER, OH

ELEVATION: 1136 TDZE: 1113

AIRPORT NAME:

WAYNE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 10, ORIG

17 DEC 2009

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	FESEK	FESEK	010	IAP	IF		FB				
	FESEK	JAVNE	020		TF		FB	1.0	006.8 (360T)	005.0	03000
	JAVNE	JAVNE	010	IAP	HF	R	FO		096.8 (090T)	006.0	03000
	PONOC	PONOC	010	IAP	IF		FB				
	PONOC	JAVNE	020		TF		FB	1.0	186.8 (180T)	005.0	03000
		JAVNE	010	FACF	IF		FB				03000
		TONSR	020	FAF	TF		FB	0.5	096.8 (090T)	006.0	02800
		COPAK	021	SDF	TF		FB	0.3	096.9 (090T)	002.9	0186001867
		RW10	030	MAP	TF		FO	0.3	096.9 (090T)	002.2	01152

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	DEHYY	040		DF		FO	1.0			03000
	DEHYY	050		HM	R	FO	2.0	277.2 (270T)	006.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	COPAK	N405229.40	W0815645.54	N4052.490	W08156.759
	DEHYY	N405228.27	W0813809.65	N4052.471	W08138.161
	FESEK	N404728.32	W0820831.54	N4047.472	W08208.526
	JAVNE	N405228.51	W0820832.64	N4052.475	W08208.544
	PONOC	N405728.69	W0820833.75	N4057.478	W08208.563
	TONSR	N405229.24	W0820035.15	N4052.487	W08200.586
	RW10	N405229.44	W0815351.53	N4052.491	W08153.859

RUNWAY DATA	THRESHOLD	
RWY	ELEVATION	TCH
RW10	01112	40

CITY AND STATE
WOOSTER, OH

ELEVATION: 1136 TDZE: 1113
 AIRPORT NAME:
WAYNE COUNTY

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 10, ORIG
17 DEC 2009

SUP:
 AMDT: **NONE**
 DATED: