

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 9, 27 STANDARD.

(2) DEPARTURE PROCEDURE:

RWY 9 - CLIMB ON A HEADING BETWEEN 087 CW TO 033 FROM DEPARTURE END OF RUNWAY TO AVOID R-2916 AND UNMARKED TETHERED BALLOON UP TO 14000 MSL.

RWY 27 - CLIMB ON A HEADING BETWEEN 087 CW TO 033 FROM DEPARTURE END OF RUNWAY TO AVOID R-2916 AND UNMARKED TETHERED BALLOON UP TO 14000 MSL.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 9, ROD ON ANTENNA, DOME ON BUILDING, POLES, AND NUMEROUS TREES BEGINNING 38' FROM DER, 199' RIGHT OF CENTERLINE, UP TO 75' AGL/82' MSL. OBSTRUCTION LIGHT ON BUILDING, POLE, AND NUMEROUS TREES BEGINNING 4' FROM DER, 220' LEFT OF CENTERLINE, UP TO 38' AGL/45' MSL.

NOTE: RWY 27, POLE AND NUMEROUS TREES BEGINNING 27' FROM DER, 116' RIGHT OF CENTERLINE, UP TO 83' AGL/90' MSL. NUMEROUS BUSHES AND TREES BEGINNING 202' FROM DER, 78' LEFT OF CENTERLINE, UP TO 37' AGL/44' MSL.

(4) CONTROLLING OBSTACLES:

RWY 9: 14,000 MSL BALLOON 244205.00N/0813031.00W.

RWY 27: 14,000 MSL BALLOON 244205.00N/0813031.00W.

(5) City, State

KEY WEST, FL

(6) Airport

KEY WEST INTL

(7) Effective Date

JUN - 8 2006

(8) Amdt. No.

1

