

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
PUNGE (IAF)	YASXU (NOPT) (FB)	087.18 / 5.00	3000	LNAV: RW17  CLIMB TO 3100 DIRECT SUBME AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD S, RT, 357.23 INBOUND. CHART FAS OBST: 1075 TREE 355703N/0950020W DOMIN TO RW17: 3.04/40. CHART AIRPORT ELEV: 874 CHART TDZ ELEV: 874
WISES (IAF)	YASXU (NOPT) (FB)	267.30 / 5.00	3000	
YASXU (IF/IAF)	DOMIN (FB)	177.24 / 6.10	2500	

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD N YASXU, RT, 177.24 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 177.23 FAF: DOMIN DIST FAF TO MAP: 4.93 THLD: 4.93
- MIN. ALT: YASXU 3000, DOMIN 2500, YELUN/2.20 NM TO RW17 1600
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 5E

EPOCH YEAR: 1995

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N/A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1380	1	506	1380	1	506	1380	1 1/2	506		NA				
CIRCLING	1520	1	646	1520	1	646	1520	1 3/4	646		NA				

NOTES:

CHART NOTE: DME/DME RNP-0.3 NA.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MUSKOGEE ALTIMETER SETTING AND INCREASE

SEE 8260-10

CITY AND STATE	ELEVATION: 874 TDZE: 874	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 1 JUN 5 2008	SUP: AMDT: ORIG: DATED 10-30-03
TAHLEQUAH, OK	AIRPORT NAME: TAHLEQUAH MUNI			

## US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES CONT.

ALL MDAS 100 FEET AND INCREASE LNAV CAT C VISIBILITY 1/4 MILE, CIRCLING CAT B 1/4 MILE AND CAT C 1/2 MILE

## TAA

	FROM	TO	ALT
1.	087/30 CW 267/30 (NOPT)	087/10 CW 267/10	3100
2.	087/10 CW 267/10	YASXU (IF/IAF) (FB)	3000
3.	267/30 CW 357/30	267/10 CW 357/10	3400
4.	267/10 CW 357/10	WISES (IAF) (FB)	3000
5.	357/30 CW 087/30	357/10 CW 087/10	3600
6.	357/10 CW 087/10	PUNGE (IAF) (FB)	3000

CITY AND STATE

TAHLEQUAH, OK

ELEVATION: 874 TDZE: 874

AIRPORT NAME:

TAHLEQUAH MUNI

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, AMDT 1

JUN 5 2008

SUP:

AMDT: ORIG

DATED: 10-30-03

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

SUP:	
AMDT:	ORIG
DATED: 10-30-03	

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	PUNGE	PUNGE	010	IAF	IF		FB				
	PUNGE	YASXU	020		TF		FB	1.0	087.2(092T)	005.0	03000
	WISES	WISES	010	IAF	IF		FB				
	WISES	YASXU	020		TF		FB	1.0	267.3(272T)	005.0	03000
	YASXU	YASXU	010		HF	R	FB		177.2(182T)	004.0	03000
		YASXU	010	FACF	IF		FB				03000
		DOMIN	020	FAF	TF		FB	0.5	177.2(182T)	006.1	02500
		YELUN	021	SDF	TF		FB	0.3	177.2(182T)	002.7	01600
		RW17	030	MAP	TF		FO	0.3	177.2(182T)	002.2	00909

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	SUBME	040		DF		FO	1.0			03100
	SUBME	050		HM	R	FO	2.0	357.2(002T)	004.0	03100

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DOMIN	N360109.58	W0950000.90	N3601.160	W09500.015
	PUNGE	N360727.57	W0950553.32	N3607.460	W09505.889
	SUBME	N354514.29	W0950046.59	N3545.238	W09500.777
	WISES	N360704.09	W0945333.29	N3607.068	W09453.555
	YASXU	N360715.99	W0945943.29	N3607.267	W09459.722
	YELUN	N355825.83	W0950008.75	N3558.431	W09500.146
	RW17	N355613.74	W0950015.08	N3556.229	W09500.251

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW17	00869	40

CITY AND STATE <b>TAHLEQUAH, OK</b>	ELEVATION: 874    TDZE: 874	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 17, AMDT 1</b>  <b>JUN 5 2008</b>	SUP:
	AIRPORT NAME: <b>TAHLEQUAH MUNI</b>			AMDT:    ORIG
				DATED: 10-30-03