

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH				
FROM	TO	COURSE AND DISTANCE	ALTITUDE					
HEBLI (IAF)	MOFEB (NOPT) (FB)	153.98 / 5.00	1900	LNAV: RW24 CLIMB TO 2000 DIRECT ODAZO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 063.79 INBOUND. CHART FAS OBST: 269 TREE 310652N/0865816W QEPGY TO RW24: 3.04/40				
CUMAT (IAF)	MOFEB (NOPT) (FB)	334.02 / 5.00	1900					
MOFEB (IF/IAF)	QEPGY (FB)	244.00 / 6.20	1900					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE MOFEB, RT, 244.00 INBOUND, 1900 FT. IN LIEU OF PT (IAF) 3. FAC: 243.95 FAF: QEPGY DIST FAF TO MAP: 5.50 THLD: 5.50 4. MIN. ALT: MOFEB 1900, QEPGY 1900 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____				MAG VAR: 1W EPOCH YEAR: 2000				
MINIMUMS								
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X			
CATEGORY =====>	A		B		C		D	
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	520	1	437	520	1	437	520	1 1/2
CIRCLING	660	1	561	660	1	561	700	2
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE PENSACOLA ALTIMETER SETTING AND INCREASE ALL MDA 100 FT; INCREASE LNAV AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE. CHART NOTE: PROCEDURE NA AT NIGHT.								
CITY AND STATE:			ELEVATION: 99 TDZE: 83		FACILITY IDENTIFIER:		PROCEDURE NO /AMDT NO /EFFECTIVE DATE:	
BREWTON, AL			AIRPORT NAME:		RNAV		RNAV (GPS) RWY 24, ORIG	
			BREWTON MUNI				11 MAR 2010	
							SUP:	
							AMDT: NONE	
							DATED	



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	154/30 CW 334/30 (NOPT) 154/8 CW 334/8	154/8 CW 334/8 MOFEB (IF/IAF) (FB)	2300 1900
2.	334/30 CW 064/30	CUMAT (IAF) (FB)	2300
3.	064/30 CW 154/30	HEBLI (IAF) (FB)	2000

QUALITY
9
CHECKED

CITY AND STATE
BREWTON, AL

ELEVATION: 99 TDZE: 83
AIRPORT NAME:
BREWTON MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 24, ORIG
11 MAR 2010

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

QUALITY
CHECKED

SUP:	
AMDT:	NONE
DATED:	