

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: GUHWO CLIMBING RIGHT TURN TO 3000 DIRECT MARN AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 276.00 INBOUND. CHART FAS OBST: 240 TOWER 364159N/1213736W UBBEP TO RW13: 3.04/50.	
ISIFU	MOVER (FB)	003.00 / 8.82	5000		
SHOEY	MOVER (FB)	044.76 / 13.60	5000		
MOVER (IAF)	EWTOF (FB)	088.38 / 7.85	3200		
EWTOF (IF)	UBBEP (FB)	131.75 / 6.15	1700		

1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)	
2. PROFILE STARTS AT EWTOF	
3. FAC: <u>131.79</u> FAF: <u>UBBEP</u> DIST FAF TO MAP: <u>4.05</u> THLD: <u>4.85</u>	
4. MIN. ALT: <u>EWTOF 3200, UBBEP 1700</u>	
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u> </u> TCH: <u>34:1 IS NOT CLEAR</u>	
8. MSA FROM: <u>GUHWO 6300</u>	
MAG VAR: 16E EPOCH YEAR: 1980	

MINIMUMS															
TAKEOFF:	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	540	1	455	540	1	455	540	1 1/4	455	540	1 1/2	455			
CIRCLING	540	1	455	540	1	455	540	1 1/2	455	760	2 1/4	675			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MONTEREY PENINSULA ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND INCREASE LNAV CAT C AND D VISIBILITY 1/4 MILE.
 SEE 8260-10

@ CAT D 800-2 1/4
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 85 TDZE: 85	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
SALINAS, CA	AIRPORT NAME:	RNAV	RNAV (GPS) RWY 13, ORIG 27 AUG 2009	AMDT: NONE
	SALINAS MUNI			DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ISIFU VIA T257 SOUTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SHOEY VIA V230 WEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MOVER VIA V25-V87 NORTHWEST BOUND.

CITY AND STATE

SALINAS, CA

ELEVATION: 85

TDZE: 85

AIRPORT NAME:

SALINAS MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, ORIG

27 AUG 2009

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE SALINAS, CA	ELEVATION: 85 TDZE: 85 AIRPORT NAME: SALINAS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 27 AUG 2009	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1	2	3	4	5	6	7	8	9	0	1	2	3

SUSAP KSNSK2SGUHWOK2EA	0 18018006325										M		

QUALITY
CHECKED

CITY AND STATE SALINAS, CA	ELEVATION: 85 TDZE: 85 AIRPORT NAME: SALINAS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 27 AUG 2009	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	PO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	ISIFU	ISIFU	010		IF		FB				
	ISIFU	MOVER	020	IAF	TF		FB	2.0	003.0 (019T)	008.8	05000
	ISIFU	EWTOF	030		TF		FB	1.0	088.4 (104T)	007.9	03200
	SHOEY	SHOEY	010		IF		FB				
	SHOEY	MOVER	020	IAF	TF		FB	2.0	044.8 (061T)	013.6	05000
	SHOEY	EWTOF	030		TF		FB	1.0	088.4 (104T)	007.9	03200
		EWTOF	010	FACF	IF		FB				03200
		UBBEP	020	FAP	TF		FB	0.5	131.8 (148T)	006.2	01700
		GUHWO	030	MAP	TF		FO	0.3	131.8 (148T)	004.1	00393

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	PO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	MARNA	040		DF	R	FO	1.0			03000
	MARNA	050		HM	R	FO	2.0	276.0 (292T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	EWTOF	N364926.12	W1214353.83	N3649.435	W12143.897
	GUHWO	N364047.67	W1213707.81	N3640.795	W12137.130
	ISIFU	N364302.89	W1215656.95	N3643.048	W12156.949
	MARNA	N364354.92	W1214847.28	N3643.915	W12148.788
	MOVER	N365123.67	W1215322.30	N3651.395	W12153.372
	SHOEY	N364445.53	W1220809.40	N3644.759	W12208.157
	UBBEP	N364413.60	W1213948.87	N3644.227	W12139.815
	RW13	N364006.99	W1213636.03	N3640.117	W12136.601

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW13	00085	50

QUALITY
CHECKED

CITY AND STATE

SALINAS, CA

ELEVATION: 85

TDZE: 85

AIRPORT NAME:

SALINAS MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, ORIG

27 AUG 2009

SUP:

AMDT: NONE

DATED: