

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
MILFORD, UT	MILFORD MUNI/BEN AND JUDY BRISCOE FIELD	05 APR 2012	2

TAKEOFF MINIMUMS:

RWY 16 – STANDARD.

RWY 34 – STANDARD WITH MINIMUM CLIMB OF 487 FT PER NM TO 6500 OR 1500-3 FOR CLIMB IN VISUAL CONDITIONS.

TEXTUAL DEPARTURE PROCEDURES:

RWY 16 – CLIMB DIRECT MLF VORTAC, THENCE...

... AIRCRAFT DEPARTING ON V235 OR V21 SOUTHBOUND PROCEED ON COURSE.

... ALL OTHER AIRCRAFT CLIMB TO 11000 ON MLF VORTAC R-168, THEN RIGHT TURN DIRECT MLF VORTAC. CONTINUE CLIMB-IN-HOLD, RT, 348.00 INBOUND TO CROSS MLF VORTAC AT OR ABOVE MEA/MCA FOR ROUTE OF FLIGHT.

RWY 34 – CLIMBING LEFT TURN TO INTERCEPT MLF VORTAC R-310 TO MLF VORTAC, THENCE....

... AIRCRAFT DEPARTING ON V235 OR V21 SOUTHBOUND; PROCEED ON COURSE.

... ALL OTHER AIRCRAFT, CLIMB-IN-HOLD, MLF VORTAC, RT, 348.00 INBOUND TO CROSS MLF VORTAC AT OR ABOVE MEA/MCA FOR ROUTE OF FLIGHT.

... OR CLIMB IN VISUAL CONDITIONS TO CROSS MILFORD MUNI/BEN AND JUDY BRISCOE FIELD AIRPORT SOUTHBOUND AT OR ABOVE 6400, THEN CLIMB ON MLF VORTAC R-345 TO MLF VORTAC. AIRCRAFT DEPARTING ON V235 AND V21 SOUTHBOUND; PROCEED ON COURSE. ALL OTHER AIRCRAFT CLIMB TO 11000 ON MLF VORTAC R-168, THEN, RIGHT TURN DIRECT MLF VORTAC. CONTINUE CLIMB-IN-HOLD, RT, 348.00 INBOUND TO CROSS MLF VORTAC AT OR ABOVE MEA/MCA FOR ROUTE OF FLIGHT.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 16, TREES BEGINNING 440 FT FROM DER, 332 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/5159 FT MSL. TREES BEGINNING 4912 FT FROM DER, 1451 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/5179 FT MSL.

NOTE: RWY 34, VEHICLES ON ROADWAY 231 FT FROM DER, ACROSS CENTERLINE, UP TO 15 FT AGL/5054 FT MSL. TREES BEGINNING 3177 FT FROM DER, 508 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/5119 FT MSL.

CONTROLLING OBSTACLES:

RWY 34: 6139 FT MSL TREE 382737.81N/1130407.57W.

RWY 34 VCOA: 6139 FT MSL TREE 382737.81N/1130407.57W.

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 16/34 – 12369 MSL AAO 382204.90N/1122216.40W; VCOA – 9582 MSL AAO 382251.20N/1124847.50W.

QUALITY
CHECKED