

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES												MISSED APPROACH			
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW06 CLIMB TO 3000 DIRECT OKUMY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 238.37 INBOUND. CHART FAS OBST: 1016 TREE 381336N/0911042W CHART FAS OBST: 1159 TREE 381223N/0911144W 1179 AAO 381112N/0911555W DISTANCE TO THLD FROM 303 HAT: 0.83 NM. CHART VDP AT 1.08 MILES TO RW06* *LNAV ONLY. WAAS CHANNEL # 82414 REFERENCE PATH ID: W06A					
NARFU (IAF)		WINIL (NOPT) (FB)		148.07 / 5.00				3000							
KAHHO (IAF)		WINIL (NOPT) (FB)		328.13 / 5.00				3000							
WINIL (IF/IAF)		BEXVE (FB)		058.11 / 6.10				2600							
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW WINIL, RT, 058.11 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>058.17</u> FAF: <u>BEXVE</u> DIST FAF TO MAP: <u>5.04</u> THLD: <u>5.04</u> 4. MIN. ALT: <u>WINIL 3000, BEXVE 2600</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>2600</u> GS ALT AT: <u>BEXVE</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u> </u>												MAG VAR: 2E		EPOCH YEAR: 1995	
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	X									
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1236	1	303	1236	1	303		NA			NA				
LNAV/VNAV DA	1488	2	555	1488	2	555		NA			NA				
LNAV MDA	1420	1	487	1420	1	487		NA			NA				
CIRCLING	1520	1	587	1520	1	587		NA			NA				
NOTES: CHART NOTE: CIRCLING TO RWY 24 NA AT NIGHT. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. SEE 8260-10															
CITY AND STATE		ELEVATION: 933 TDZE: 933				FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
SULLIVAN, MO		AIRPORT NAME:				RNAV		RNAV (GPS) RWY 6, ORIG				AMDT: NONE			
		SULLIVAN REGIONAL						27 AUG 2009				DATED			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART PROFILE NOTE: VGS1 AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING ROLLA NATIONAL ALTIMETER SETTING.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROLLA NATIONAL ALTIMETER SETTING AND INCREASE ALL DA 98 FEET AND ALL MDA 100 FEET, INCREASE LPV CAT A AND B VISIBILITY 1/2 MILE AND LNAV/VNAV CAT A AND B VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	328/30 CW 148/30 (NOPT)	WINIL (IF/IAF) (FB)	3000
2.	148/30 CW 238/30	NARFU (IAF) (FB)	3000
3.	238/30 CW 328/30	KAHHO (IAF) (FB)	3100

CITY AND STATE

SULLIVAN, MO

ELEVATION: 933

TDZE: 933

AIRPORT NAME:

SULLIVAN REGIONAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 6, ORIG

27 AUG 2009

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KUUU
RUNWAY	RW06
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W06A
LTP/FTP LATITUDE	381349.4855N
LTP/FTP LONGITUDE	0911015.9005W
LTP/FTP ELLIPSOIDAL HEIGHT	+02539
FPAP LATITUDE	381433.7700N
FPAP LONGITUDE	0910837.7300W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1376
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

7AE78525

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02844
FPAP ORTHOMETRIC HEIGHT	+02844

CITY AND STATE SULLIVAN, MO	ELEVATION: 933 TDZE: 933 AIRPORT NAME: SULLIVAN REGIONAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG 27 AUG 2009	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE SULLIVAN, MO	ELEVATION: 933 TDZE: 933	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG 27 AUG 2009	SUP:
	AIRPORT NAME:			AMDT: NONE
	SULLIVAN REGIONAL			DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	KAHHO	KAHHO	010	IAF	IF		FB				
	KAHHO	WINIL	020		TF		FB	1.0	328.1 (330T)	005.0	03000
	NARFU	NARFU	010	IAF	IF		FB				
	NARFU	WINIL	020		TF		FB	1.0	148.1 (150T)	005.0	03000
	WINIL	WINIL	010	IAF	HF	R	FO		058.1 (060T)	004.0	03000
		WINIL	010	FACF	IF		FB				03000
		BEXVE	020	FAF	TF		FB	0.5	058.1 (060T)	006.1	02600
		RW06	030	MAP	TF		FO	0.3	058.2 (060T)	005.0	00973

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	OKUMY	040		DF		FO	1.0			03000
	OKUMY	050		HM	R	FO	2.0	238.4 (240T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BEXVE	N381119.09	W0911548.74	N3811.318	W09115.812
	KAHHO	N380356.22	W0911921.93	N3803.937	W09119.366
	NARFU	N381236.93	W0912541.04	N3812.616	W09125.684
	OKUMY	N381942.76	W0905710.22	N3819.713	W09057.170
	WINIL	N380816.62	W0912231.30	N3808.277	W09122.522
	RW06	N381349.49	W0911015.90	N3813.825	W09110.265

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW06	00933	40

CITY AND STATE SULLIVAN, MO	ELEVATION: 933 TDZE: 933 AIRPORT NAME: SULLIVAN REGIONAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, ORIG 27 AUG 2009	SUP:
				AMDT: NONE
				DATED: