

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
TIMDE (IAF)	BIBBA (NOPT) (FB)	107.37 / 5.00	4000	LPV: DA LNAV: RW20
WALIX (IAF)	BIBBA (NOPT) (FB)	287.53 / 5.00	4000	CLIMB TO 4000 DIRECT UBISE AND ON TRACK 193.17 TO AFRED AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000.
BIBBA (IF/IAF)	LOCET (FB)	197.45 / 1.90	3500	
LOCET	AKAYU (FB)	197.45 / 4.80	2200	
AKAYU (FAF)	RW20 (MAP) (FO)	197.45 / 5.84		
RW20 (MAP)	666 MSL	197.45		ADDITIONAL FLIGHT DATA: HOLD S, RT, 013.46 INBOUND. CHART FAS OBST: 1099 TREE 435519N/0732547W DISTANCE TO THLD FROM 395 HAT: 1.12 NM. WAAS CHANNEL # 53716 REFERENCE PATH ID: W20A LTP HAE: 51.6 M
666 MSL	UBISE (FB)			
UBISE	AFRED (FO)	193.17/4.00	4000	

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD N BIBBA, RT, 197.45 INBOUND, 4000 FT. IN LIEU OF PT (IAF)				
3. FAC:	197.45	FAF: AKAYU	DIST FAF TO MAP:		5.84 THLD: 5.84
4. MIN. ALT:	BIBBA 4000, LOCET 3500, AKAYU 2200				
5. DIST TO THLD FROM OM:	MM:	IM:	150 HAT:	100 HAT:	GS ANT:
6. MIN GS INCPT:	2200	GS ALT AT: AKAYU	OM:	MM:	IM:
7. GS ANGLE:	3.00	TCH: 45.0 34:1 IS NOT CLEAR			
8. MSA FROM:					

EPOCH YEAR: 2000

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: N/A

X

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	666	1 1/2	395	666	1 1/2	395		NA			NA				
LNAV MDA	1420	1 1/4	1149	1420	1 1/2	1149		NA			NA				
CIRCLING	1420	1 1/4	1147	1420	1 1/2	1147		NA			NA				

CHART NOTE: WHEN VGS1 INOP, STRAIGHT-IN/CIRCLING RWY 20 NA AT NIGHT.

DATED 07/10/2003

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	107/30 CW 288/30 (NOPT)	107/8 CW 288/8	7600
2.	107/8 CW 288/8	BIBBA (IF/IAF) (FB)	4000
3.	288/30 CW 017/30	288/10 CW 017/10	6000
4.	288/10 CW 017/10	WALIX (IAF) (FB)	4800
5.	017/30 CW 107/30	017/8 CW 107/8	7600
6.	017/8 CW 107/8	TIMDE (IAF) (FB)	4900



CITY AND STATE

TICONDEROGA, NY

ELEVATION: 273

TDZE: 271

AIRPORT NAME:

TICONDEROGA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 20, AMDT 1

10 MAR 2011

SUP:

AMDT: ORIG

DATED: 07/10/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER 4B6
RUNWAY RW20
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W20A
LTP/FTP LATITUDE 435258.0975N
LTP/FTP LONGITUDE 0732446.1195W
LTP/FTP ELLIPSOIDAL HEIGHT +00516
FPAP LATITUDE 435129.0700N
FPAP LONGITUDE 0732451.3800W
THRESHOLD CROSSING HEIGHT (TCH) 00045.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1520
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

6D981D97

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +00807
FPAP ORTHOMETRIC HEIGHT +00807

CITY AND STATE

TICONDEROGA, NY

ELEVATION: 273

TDZE: 271

AIRPORT NAME:

TICONDEROGA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 20, AMDT 1

10 MAR 2011

SUP:

AMDT: ORIG

DATED: 07/10/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 4B6 K6FR20	ABIBBA	010BIBBAK6EA0EE	AR	HF			19750040		+ 04000	18000		A JS	
SUSAP 4B6 K6FR20	ATIMDE	010TIMDEK6EA0E	A	IF						18000		A JS	
SUSAP 4B6 K6FR20	ATIMDE	020BIBBAK6EA0EE	B	010TF			10740050		+ 04000			A JS	
SUSAP 4B6 K6FR20	AWALIX	010WALIXK6EA0E	A	IF						18000		A JS	
SUSAP 4B6 K6FR20	AWALIX	020BIBBAK6EA0EE	B	010TF			28750050		+ 04000			A JS	
SUSAP 4B6 K6FR20	R	010BIBBAK6EA0E	I	IF					+ 04000	18000		A JS	
SUSAP 4B6 K6FR20	R	011LOCETK6EA0E	S	051TF			19750019		+ 03500			A JS	
SUSAP 4B6 K6FR20	R	020AKAYUK6EA1E	F	051TF			19750048		+ 02200			A JS	
SUSAP 4B6 K6FR20	R	020AKAYUK6EA2WALPV			N	ALNAV						JS	
SUSAP 4B6 K6FR20	R	030RW20 K6PGOGY	M	031TF			19750058		00310	-300		A JS	
SUSAP 4B6 K6FR20	R	040	0	M	010CA		1975		+ 00666			A JS	
SUSAP 4B6 K6FR20	R	050UBISEK6EA0E		010DF								A JS	
SUSAP 4B6 K6FR20	R	060AFREDK6EA0EY		010TF			1932		+ 04000			A JS	
SUSAP 4B6 K6FR20	R	070AFREDK6EA0EE		R02OHM			01350040		+ 04000			A JS	

[illegible]

CITY AND STATE TICONDEROGA, NY	ELEVATION: 273 AIRPORT NAME: TICONDEROGA MUNI	TDZE: 271	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1 10 MAR 2011	SUP:	
					AMDT:	ORIG
					DATED:	07/10/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	ORIG
DATED:	07/10/2003