

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
AVIBE (IAF)	JAVOT (NOPT) (FB)	077.92 / 5.00	2100	LNAV/VNAV: DA LNAV: RW35 CLIMB TO 2000 DIRECT AVORE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 167.93 INBOUND. CHART FAS OBST: 379 TREE 330441N/0945731W CHART FAS OBST: 589 TOWER 330238N/0945729W CHART VDP AT 1.62 MILES TO RW35* *LNAV ONLY. DIST TO THLD FROM 340 HAT: 0.99 NM CHART AIRPORT ELEVATION: 364
BUNLE (IAF)	JAVOT (NOPT) (FB)	258.02 / 5.00	2100	
JAVOT (IF/IAF)	CENSO (FB)	347.97 / 6.10	2000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S JAVOT, RT, 347.97 INBOUND, 2100 FT. IN LIEU OF PT (IAF)**
- FAC: 347.96 FAF: CENSO DIST FAF TO MAP: 5.00 THLD: 5.00
- MIN. ALT: **JAVOT 2100, CENSO 2000**
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2000 GS ALT AT: CENSO OM: MM: IM:
- GS ANGLE: 3.00 TCH: 44.0 **34:1 IS CLEAR**
- MSA FROM:

MAG VAR: 4E EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A		STANDARD @								
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV/VNAV DA	700	1 1/4	340	700	1 1/4	340	700	1 1/4	340	700	1 1/4	340			
LNAV MDA	900	1	540	900	1	540	900	1 1/2	540	900	1 3/4	540			
CIRCLING	900	1	536	900	1	536	900	1 1/2	536	920	2	556			

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTES: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PARIS ALTIMETER SETTING AND INCREASE ALL DA/MDA 120 FEET, INCREASE LNAV/VNAV VISIBILITIES 1/2 MILE ALL CATS, LNAV VISIBILITIES 1/4
 SEE 8260-10

CITY AND STATE MOUNT PLEASANT, TX	ELEVATION: 364 TDZE: 360 AIRPORT NAME: MOUNT PLEASANT RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 15 JAN 2009	SUP:
				AMDT: ORIG-B
				DATED 09/05/2003

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

MILE ALL CATS AND CIRCLING VISIBILITIES 1/4 MILE ALL CATS. VDP AND BARO-VNAV NA WHEN USING PARIS
ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	258/30 CW 078/30 (NOPT)	258/10 CW 078/10	2600
2.	258/10 CW 078/10	JAVOT (IF/IAF) (FB)	2100
3.	078/30 CW 168/30	AVIBE (IAF) (FB)	2600
4.	168/30 CW 258/30	BUNLE (IAF) (FB)	2500

CITY AND STATE

MOUNT PLEASANT, TX

ELEVATION: 364

TDZE: 360

AIRPORT NAME:

MOUNT PLEASANT RGNL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1

15 JAN 2009

SUP:

AMDT: ORIG-B

DATED: 09/05/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	ORIG-B
DATED:	09/05/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	AVIBE	AVIBE	010	IAF	IF		FB				
	AVIBE	JAVOT	020		TF		FB	1.0	077.9(082T)	005.0	02100
	BUNLE	BUNLE	010	IAF	IF		FB				
	BUNLE	JAVOT	020		TF		FB	1.0	258.0(262T)	005.0	02100
	JAVOT	JAVOT	010		HF	R	FB		348.0(352T)	004.0	02100
		JAVOT	010	FACF	IF		FB				02100
		CENSO	020	FAF	TF		FB	0.5	348.0(352T)	006.1	02000
		RW35	030	MAP	TF		FO	0.3	348.0(352T)	005.0	00385

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	AVORE	040		DF		FO	1.0			02000
	AVORE	050		HM	R	FO	2.0	167.9(172T)	004.0	02000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	AVIBE	N325336.56	W0950139.38	N3253.609	W09501.656
	AVORE	N331713.91	W0945938.51	N3317.315	W09459.642
	BUNLE	N325500.54	W0944953.70	N3255.009	W09449.895
	CENSO	N330021.76	W0945647.41	N3300.363	W09456.790
	JAVOT	N325418.69	W0945546.59	N3254.312	W09455.777
	RW35	N330519.42	W0945737.37	N3305.324	W09457.623

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00341	44

CITY AND STATE
MOUNT PLEASANT, TX

ELEVATION: 364 TDZE: 360
AIRPORT NAME:
MOUNT PLEASANT RGNL

**FACILITY
IDENTIFIER:**
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 35, AMDT 1
15 JAN 2009

SUP:
AMDT: ORIG-B
DATED: 09/05/2003