

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES																	MISSED APPROACH									
FROM				TO				COURSE AND DISTANCE				ALTITUDE		LP: RW07 LNAV: RW07												
JISRA (IF/IAF)				VEMSY (TF) (FB) (RNP 1.00)				070.93 / 4.69				3400		CLIMB TO 4600 DIRECT HERTO AND HOLD, CONTINUE CLIMB IN HOLD TO 4600.												
VEMSY (FAF)				OMKUQ/3.40 NM TO RW07 (TF) (FB) (RNP 0.30)				070.98 / 3.26																		
OMKUQ/3.40 NM TO RW07				RW07 (MAP) (TF) (FO) (RNP 0.30)				070.98 / 3.40						ADDITIONAL FLIGHT DATA: HOLD E, RT, 251.18 INBOUND. CHART FAS OBST: 1554 TREE 362706N/0825432W CHART FAS OBST: 1869 TREE 362653N/0825632W 2077 AAO 362451N/0830045W WAAS CHANNEL # 58040 REFERENCE PATH ID: W07A CHART CIRCLING ICON. VEMSY TO RW07: 3.00/25. LTP HAE: 351 M												
RW07 (MAP)				1655 MSL (CA)				070.98																		
1655 MSL				HERTO (DF) (FO) (RNP 1.00)								4600														
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																										
2. HOLD W JISRA, RT, 070.93 INBOUND, 4300 FT. IN LIEU OF PT (IAF)																										
3. FAC: 070.98 FAF: VEMSY DIST FAF TO MAP: 6.66 THLD: 6.66																										
4. MIN. ALT: JISRA 4300, VEMSY 3400, OMKUQ/3.40 NM TO RW07 2360																										
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																										
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																										
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																										
8. MSA FROM: _____																										
MAG VAR: 7W EPOCH YEAR: 2020																										
MINIMUMS																										
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT																										
ALTERNATE: N A X																										
CATEGORY ==>		A			B			C			D			E												
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA											
LP MDA	1820	1	565	1820	1	565	1820	1 5/8	565		NA															
LNAV MDA	2040	1	785	2040	1 1/4	785	2040	2 1/2	785		NA															
CIRCLING	2180	1 1/4	925	2180	1 1/4	925	2320	3	1065		NA															
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE TRI-CITIES RGNL ALTIMETER SETTING AND INCREASE ALL MDA 120FT, INCREASE LP CAT C VISIBILITY 3/8 SM, INCREASE LNAV CAT A AND (CONTINUED ON PAGE 2)																										
CITY AND STATE ROGERSVILLE, TN				ELEVATION: 1255 TDZE: 1255 AIRPORT NAME: HAWKINS COUNTY				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 17 AUGUST 2017						SUP: AMDT: NONE DATED										

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CIRCLING CAT B VISIBILITY 1/4 SM.

CHART NOTE: RWY 7, 25 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	341/30 CW 161/30 (NOPT)	341/15 CW 161/15	5700
	341/15 CW 161/15	JISRA (IF/IAF) (FB)	4300
2.	161/30 CW 341/30	161/15 CW 341/15	6400
	161/15 CW 341/15	JISRA (IF/IAF) (FO)	4300

CITY AND STATE
ROGERSVILLE, TN

ELEVATION: 1255 TDZE: 1255
AIRPORT NAME:
HAWKINS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 7, ORIG
17 AUGUST 2017

SUP: **QUALITY 10 CHECKED**
AMDT: **NONE**
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRVN
RUNWAY	RW07
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	362719.7075N
LTP/FTP LONGITUDE	0825325.4015W
LTP/FTP ELLIPSOIDAL HEIGHT	+03510
FPAP LATITUDE	362758.7390N
FPAP LONGITUDE	0825146.0760W
THRESHOLD CROSSING HEIGHT (TCH)	00025.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1688
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 C0B6491E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+03823
FPAP ORTHOMETRIC HEIGHT	+03823

CITY AND STATE
ROGERSVILLE, TN

ELEVATION: 1255 TDZE: 1255
AIRPORT NAME:
HAWKINS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 7, ORIG
17 AUGUST 2017

SUP: **QUALITY
10
CHECKED**
AMDT: **NONE**
DATED: