

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES													MISSED APPROACH																
FROM				TO				COURSE AND DISTANCE						ALTITUDE		LP: RW25 LNAV: RW25													
HERTO (IF/IAF)				DOKDE (TF) (FB) (RNP 1.00)				251.18 / 5.00						3200		CLIMB TO 4300 DIRECT JISRA AND HOLD.													
DOKDE (FAF)				RUFFE/3.30 NM TO RW25 (TF) (FB) (RNP 0.30)				251.13 / 2.80																					
RUFFE/3.30 NM TO RW25				RW25 (MAP) (TF) (FO) (RNP 0.30)				251.13 / 3.30																					
RW25 (MAP)				1655 MSL (CA)				251.13						4300															
1655 MSL				JISRA (DF) (FO) (RNP 1.00)												ADDITIONAL FLIGHT DATA: HOLD W, RT, 070.93 INBOUND. CHART FAS OBST: 1469 TREE 362837N/0825051W CHART FAS OBST: 1639 TREE 362827N/0825144W 1542 AAO 363045N/0824645W 1630 AAO 363103N/0824639W WAAS CHANNEL # 69340 REFERENCE PATH ID: W25A CHART CIRCLING ICON. DOKDE TO RW25: 3.00/28. LTP HAE: 343.5 M													
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																				MAG VAR: 7W EPOCH YEAR: 2020									
2. HOLD E HERTO, RT, 251.18 INBOUND, 4600 FT. IN LIEU OF PT (IAF)																													
3. FAC: 251.13 FAF: DOKDE DIST FAF TO MAP: 6.10 THLD: 6.10																													
4. MIN. ALT: HERTO 4600, DOKDE 3200, RUFFE/3.30 NM TO RW25 2300																													
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																													
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																													
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																													
8. MSA FROM: _____																													
MINIMUMS																													
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X																			
CATEGORY =====>		A			B			C			D			E															
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA														
LP MDA	1720	1	466	1720	1	466	1720	1 3/8	466		NA																		
LNAV MDA	1900	1	646	1900	1	646	1900	1 7/8	646		NA																		
CIRCLING	2180	1 1/4	925	2180	1 1/4	925	2320	3	1065		NA																		
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE TRI-CITIES RGNL ALTIMETER SETTING AND INCREASE ALL MDA 120FT, INCREASE LP CAT C VISIBILITY 3/8 SM, LNAV CAT B VISIBILITY 1/4 (CONTINUED ON PAGE 2)																QUALITY 10 CHECKED													
CITY AND STATE ROGERSVILLE, TN			ELEVATION: 1255 TDZE: 1254 AIRPORT NAME: HAWKINS COUNTY				FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, ORIG 17 AUGUST 2017								SUP: AMDT: NONE DATED											

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

SM, CAT C VISIBILITY 5/8 SM, AND INCREASE CIRCLING CAT B VISIBILITY 1/4 SM.

CHART NOTE: RWY 7, 25 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	161/30 CW 341/30 (NOPT)	161/5 CW 341/5	6800
	161/5 CW 341/5	HERTO (IF/IAF) (FB)	4600
2.	341/30 CW 161/30	341/5 CW 161/5	6800
	341/5 CW 161/5	HERTO (IF/IAF) (FO)	4600

QUALITY
10

CITY AND STATE ROGERSVILLE, TN	ELEVATION: 1255 TDZE: 1254 AIRPORT NAME: HAWKINS COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, ORIG 17 AUGUST 2017	SUP: CHECKED
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRVN
RUNWAY	RW25
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W25A
LTP/FTP LATITUDE	362734.8565N
LTP/FTP LONGITUDE	0825246.8535W
LTP/FTP ELLIPSOIDAL HEIGHT	+03435
FPAP LATITUDE	362655.8165N
FPAP LONGITUDE	0825426.1655W
THRESHOLD CROSSING HEIGHT (TCH)	00028.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1688
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

D85D26C9

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+03748
FPAP ORTHOMETRIC HEIGHT	+03748

QUALITY
10

CHECKED

CITY AND STATE

ROGERSVILLE, TN

ELEVATION: 1255

TDZE: 1254

AIRPORT NAME:

HAWKINS COUNTY

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 25, ORIG

17 AUGUST 2017

SUP:

AMDT:

NONE

DATED: