

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
SKIDS	HESUD (FB)	108.02 / 45.84	2100	LPV: DA LNAV/VNAV: DA LNAV: RW32
BETZY	FIKIP (FB)	163.48 / 15.90	2000	
HESUD (IAF)	JAMWU (FB)	049.47 / 5.00	2000	CLIMB TO 2000 DIRECT COPIR AND HOLD.
FIKIP (IAF)	JAMWU (FB)	229.55 / 5.00	2000	
JAMWU (IF)	EKXES (FB)	319.51 / 6.20	1400	ADDITIONAL FLIGHT DATA: HOLD NW, RT, 139.39 INBOUND. CHART FAS OBST: 164 TOWER 280353N/0970233W CHART FAS OBST: 186 TANK 280337N/0970234W CHART A-632B/D. CHART KINGSVILLE 4 MOA. DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 1.17 MILES TO RW32* *LNAV ONLY. WAAS CHANNEL # 45917 REFERENCE PATH ID: W32A

- PT NA SIDE OF COURSE OUTBOUND FT WITHIN        MILES OF        (IAF)
- PROFILE STARTS AT JAMWU
- FAC: 319.48 FAF: EKXES DIST FAF TO MAP: 4.15 THLD: 4.15
- MIN. ALT: JAMWU 2000, EKXES 1400
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT: 1400 GS ALT AT: EKXES 1400 OM:        MM:        IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR
- MSA FROM: RW32 2100

MAG VAR: 6E EPOCH YEAR: 2000

MINIMUMS																
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: NA	STANDARD @											
CATEGORY	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	274	1	250	274	1	250	274	1	250		NA					
LNAV/VNAV DA	508	1 3/4	484	508	1 3/4	484	508	1 3/4	484		NA					
LNAV MDA	420	1	396	420	1	396	420	1	396		NA					
CIRCLING	500	1	476	500	1	476	500	1 1/2	476		NA					

NOTES:  
CHART NOTE: BARO-VNAV NA WHEN USING INGLESIDE ALTIMETER SETTING.  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F).  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE ROCKPORT, TX	ELEVATION: 24 TDZE: 24 AIRPORT NAME: ARANSAS COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 32, ORIG 03 JUN 2010	SUP: AMDT: NONE DATED
--------------------------------	---	---------------------------------	--	-----------------------------

QUALITY  
CHECKED

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES CONT.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: PROCEDURE NA FOR ARRIVALS AT SKIDS ON V163 NORTHWEST BOUND, AND ARRIVALS AT BETZY ON V20-70 NORTHEAST BOUND.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE INGLESIDE ALTIMETER SETTING AND INCREASE ALL DA 33 FEET AND ALL MDA 40 FEET, INCREASE RNAV CAT C VISIBILITY 1/4 MILE.

CHART NOTE: VDP NA WITH INGLESIDE ALTIMETER SETTING.

QUALITY  
4  
CHECKED

CITY AND STATE

ROCKPORT, TX

ELEVATION: 24 TDZE: 24

AIRPORT NAME:

ARANSAS COUNTY

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 32, ORIG

03 JUN 2010

SUP:

AMDT: NONE

DATED:

**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION****DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRKP
RUNWAY	RW32
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W32A
LTP/FTP LATITUDE	280452.4220N
LTP/FTP LONGITUDE	0970233.7395W
LTP/FTP ELLIPSOIDAL HEIGHT	-00198
FPAP LATITUDE	280606.0100N
FPAP LONGITUDE	0970330.8600W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1216
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

**CRC REMAINDER**

5D9B5ECE

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00070
FPAP ORTHOMETRIC HEIGHT	+00070

QUALITY  
CHECKED

CITY AND STATE ROCKPORT, TX	ELEVATION: 24 TDZE: 24 AIRPORT NAME: ARANSAS COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 32, ORIG 03 JUN 2010	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KRKPK4FR32	ABETZY	010BETZYK4EA0E	IF						18000		A JS	
SUSAP	KRKPK4FR32	ABETZY	020FIKIPK4EA0E	A 020TF		16350159		+ 02000				A JS	
SUSAP	KRKPK4FR32	ABETZY	030JAMWUK4EA0EE	B 010TF		22960050		+ 02000				A JS	
SUSAP	KRKPK4FR32	ASKIDS	010SKIDSK4EA0E	IF						18000		A JS	
SUSAP	KRKPK4FR32	ASKIDS	020HESUDK4EA0E	A 020TF		10800458		+ 02100				A JS	
SUSAP	KRKPK4FR32	ASKIDS	030JAMWUK4EA0EE	E 010TF		04950050		+ 02000				A JS	
SUSAP	KRKPK4FR32	R	010JAMWUK4EA0E	I IF						18000		A JS	
SUSAP	KRKPK4FR32	R	020EKXESK4EA1E	F 051TF		31950062		+ 01400			RW32	K4PGA	JS
SUSAP	KRKPK4FR32	R	020EKXESK4EA2WALFV		ALNAV/VNAV	ALNAV							JS
SUSAP	KRKPK4FR32	R	030RW32	K4PG0GY M 031TF		31950042		00063		-300		A JS	
SUSAP	KRKPK4FR32	R	040	G M 010CA		3195		+ 00274				A JS	
SUSAP	KRKPK4FR32	R	050COPIRK4EA0EY	010DF				+ 02000				A JS	
SUSAP	KRKPK4FR32	R	060COPIRK4EA0EE	R020HM		13940040		+ 02000				A JS	

[illegible]

QUALITY  
1  
CHECKED

CITY AND STATE  ROCKPORT, TX	ELEVATION: 24      TDZE: 24  AIRPORT NAME:  ARANSAS COUNTY	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 32, ORIG  03 JUN 2010	SUP:
				AMDT:      NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY  
1  
CHECKED

PAGE 5 OF 5 PAGES