

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 2300 THEN CLIMBING LEFT TURN TO 3400 DIRECT FEBNO AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1675 TREE 395004N/0974020W CHART FAS OBST: 1725 TREE 395219N/0973954W DISTANCE TO THLD FROM 295 HATH: 0.80 NM. WAAS CHANNEL # 87025 REFERENCE PATH ID: W18A LTP HAE: 437.8 M											
GADWY (IAF)	FEBNO (NOPT) (FB)	218.48 / 31.45	3400												
FEBNO (IF/IAF)	WUPIK (FB)	174.54 / 6.20	3200												
WUPIK (FAF)	ATIJA/2.80 NM TO RW18 (FB)	174.51 / 2.33													
ATIJA/2.80 NM TO RW18	RW18 (MAP) (FO)	174.51 / 2.80													
RW18 (MAP)	2300 MSL	174.51	2300												
2300 MSL	FEBNO (FO)		3400												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 7E EPOCH YEAR: 1985											
2. HOLD N FEBNO, RT, 174.51 INBOUND, 3400 FT. IN LIEU OF PT (IAF)															
3. FAC: <u>174.51</u> FAF: <u>WUPIK</u> DIST FAF TO MAP: <u>5.13</u> THLD: <u>5.13</u>															
4. MIN. ALT: FEBNO 3400, WUPIK 3200, ATIJA/2.80 NM TO RW18 2440*															
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>															
6. MIN GS INCPT: <u>3200</u> GS ALT AT: <u>WUPIK 3200</u> OM: <u> </u> MM: <u> </u> IM: <u> </u>															
7. GS ANGLE: <u>3.00</u> TCH: <u>41.0</u> 34:1 IS NOT CLEAR															
8. MSA FROM: <u>RW18 3900</u>															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1819	1	295	1819	1	295	1819	1	295		NA				
LNAV/VNAV DA	1890	1 1/4	366	1890	1 1/4	366	1890	1 1/4	366		NA				
LNAV MDA	2020	1	496	2020	1	496	2020	1 3/8	496		NA				
CIRCLING	2020	1	482	2020	1	482	2020	1 1/2	482		NA				
NOTES: CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 36 NA AT NIGHT. CHART NOTE: BARO-VNAV NA. CHART NOTE: USE CONCORDIA ALTIMETER SETTING; WHEN NOT RECEIVED, USE HEBRON ALTIMETER SETTING AND INCREASE ALL DA 12 FEET AND ALL MDA 20 FEET. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 1538 THRE: 1524		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
BELLEVILLE, KS		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 18, ORIG				AMDT: NONE					
		BELLEVILLE MUNI				20 OCT 2011				DATED					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN VGSINOP, STRAIGHT-IN/CIRCLING RWY 18 PROCEDURE NA AT NIGHT.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GADWY ON V50 EASTBOUND.

*LNAV ONLY

QUALITY
3
CHECKED

CITY AND STATE

BELLEVILLE, KS

ELEVATION: 1538

THRE: 1524

AIRPORT NAME:

BELLEVILLE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

20 OCT 2011

SUP:

AMDT: NONE

DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KRPB
RUNWAY RW18
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W18A
LTP/FTP LATITUDE 394923.4700N
LTP/FTP LONGITUDE 0973936.5800W
LTP/FTP ELLIPSOIDAL HEIGHT +04378
FPAP LATITUDE 394754.3300N
FPAP LONGITUDE 0973939.6300W
THRESHOLD CROSSING HEIGHT (TCH) 00041.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1680
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

055AB90B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K3
LTP ORTHOMETRIC HEIGHT +04645
FPAP ORTHOMETRIC HEIGHT +04645

QUALITY
1
CHECKED

CITY AND STATE

BELLEVILLE, KS

ELEVATION: 1538

THRE: 1524

AIRPORT NAME:

BELLEVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

20 OCT 2011

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
1
CHECKED

CITY AND STATE BELLEVILLE, KS	ELEVATION: 1538 THRE: 1524	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 20 OCT 2011	SUP:	
	AIRPORT NAME: BELLEVILLE MUNI			AMDT:	NONE
				DATED:	

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
1
CHECKER

ELEVATION: 1538 THRE: 1524
AIRPORT NAME:
BELLEVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, ORIG
20 OCT 2011

SUP:	
AMDT:	NONE
DATED:	