

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE			ALTITUDE		RW36							
ZILIB (IF/IAF)		JAGGY (TF) (FB) (RNP 1.00)		005.38 / 6.59			3500		CLIMB TO 4000 DIRECT ZOLPU AND HOLD.							
JAGGY (FAF)		RW36 (MAP) (TF) (FO) (RNP 0.30)		005.38 / 4.66												
RW36 (MAP)		2094 MSL														
2094 MSL		ZOLPU (DF) (FO)					4000		ADDITIONAL FLIGHT DATA: HOLD N, RT, 185.38 INBOUND. CHART FAS OBST: 1913 COMM TWR 361846N/0845613W 1940 AAO 361606N/0845732W. CHART CIRCLING ICON. CHART PROFILE NOTE: VISUAL SEGMENT-OBSTACLES. CHART CROSSVILLE ASOS.							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD S ZILIB, RT, 005.38 INBOUND, 4400 FT. IN LIEU OF PT (IAF)																
3. FAC: 005.38 FAF: JAGGY DIST FAF TO MAP: 4.66 THLD: 4.66																
4. MIN. ALT: ZILIB 4400, JAGGY 3500																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: _____																
8. MSA FROM: _____																
MAG VAR: 5W EPOCH YEAR: 2020																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X						
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
CIRCLING	2180	1	486	2260	1	566	2340	1 3/4	646		NA					
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF 122.8, WHEN NOT RECEIVED, USE CROSSVILLE ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND CAT C VISIBILITY 1/2 SM. CHART NOTE: CIRCLING RWY 18 NA AT NIGHT.																
CITY AND STATE JAMESTOWN TN		ELEVATION: 1694 TDZE: AIRPORT NAME: JAMESTOWN MUNI			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, ORIG 22 JUNE 2017					SUP: AMDT: NONE DATED				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	275/30 CW 095/30 (NOPT)	275/15 CW 095/15 (FO)	6000
2.	275/15 CW 095/15	ZILIB (IF/IAF) (FB)	4400
3.	095/30 CW 275/30	095/15 CW 275/15	6000
4.	095/15 CW 275/15	ZILIB (IF/IAF) (FO)	4400

QUALITY
9
CHECKED

CITY AND STATE JAMESTOWN, TN	ELEVATION: 1694 AIRPORT NAME: JAMESTOWN MUNI	TDZE: JAMESTOWN MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, ORIG 22 JUNE 2017	SUP:
					AMDT: NONE
					DATED: