

| | | | | | | | | | | | | | | | | |
|--|------|-----------------|---------|---------------------|-----|----------------------|------|--|---------|--|-------|---------|-----|------------------|---------|--|
| U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27 | | | | | | | | Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR. | | | | | | | | |
| TERMINAL ROUTES | | | | | | | | | | MISSED APPROACH | | | | | | |
| FROM | | TO | | COURSE AND DISTANCE | | | | ALTITUDE | | MAP: 4.43 MILES AFTER DJD NDB | | | | | | |
| NELLO INT | | DJD NDB | | 198.36 / 15.22 | | | | 5000 | | CLIMBING RIGHT TURN TO 3300 DIRECT DJD NDB AND HOLD. | | | | | | |
| | | | | | | | | | | ADDITIONAL FLIGHT DATA: HOLD SW, RT, 047.27 INBOUND. FAS OBST: 1579 AAO 341655N/0842931W DJD NDB TO RW05: 3.11/30. | | | | | | |
| 1. PT <u>L</u> SIDE OF COURSE <u>227.27</u> OUTBOUND <u>3300</u> FT WITHIN <u>10</u> MILES OF <u>DJD NDB</u> (IAF) | | | | | | | | | | | | | | | | |
| 2. | | | | | | | | | | | | | | | | |
| 3. FAC <u>047.27</u> FAF <u>DJD NDB</u> DIST FAF TO MAP <u>4.43</u> THLD <u>4.43</u> | | | | | | | | | | | | | | | | |
| 4. MIN. ALT <u>DJD NDB 2700</u> | | | | | | | | | | | | | | | | |
| 8. MSA FROM: <u>DJD NDB 070-260 3200, 260-070 5000</u> | | | | | | | | | | MAG VAR: 5W | | | | EPOCH YEAR: 2010 | | |
| MINIMUMS | | | | | | | | | | | | | | | | |
| TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT | | | | | | | | ALTERNATE: N A | | STANDARD @ | | | | | | |
| CATEGORY ==> | | A | | | B | | | C | | | D | | | E | | |
| | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | |
| S-5 | 1880 | 1 | 675 | 1880 | 1 | 675 | 1880 | 1 7/8 | 675 | 1880 | 1 7/8 | 675 | | | | |
| CIRCLING | 1880 | 1 | 661 | 1880 | 1 | 661 | 1880 | 1 7/8 | 661 | 1880 | 2 | 661 | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MARIETTA ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET; INCREASE S-5 CAT B AND CIRCLING CATS B AND C VISIBILITY 1/4 MILE, INCREASE S-5 (SEE FORM 8260-10) <div style="text-align: right;">@ NA WHEN LOCAL WEATHER NOT AVAILABLE.</div> <div style="text-align: right; border: 1px solid black; border-radius: 50%; padding: 5px; display: inline-block;"> QUALITY A CHECKED </div> | | | | | | | | | | | | | | | | |
| CITY AND STATE | | ELEVATION: 1219 | | THRE: 1205 | | FACILITY IDENTIFIER: | | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: | | | | SUP | | NDB RWY 4 | | |
| CANTON, GA | | AIRPORT NAME: | | CHEROKEE COUNTY | | DJD | | 25 AUG 2011 | | | | AMDT | | 3A | | |
| | | | | | | | | | | | | DATE | | 01/15/2009 | | |

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are *minimum altitudes* unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CATS C AND D VISIBILITY 1/8 MILE.

CHART NOTE: CIRCLING RWY 23 NA AT NIGHT.

QUALITY
4
CHECKED

CITY AND STATE

CANTON, GA

ELEVATION: 1219

THRE: 1205

AIRPORT NAME:

CHEROKEE COUNTY

FACILITY
IDENTIFIER:

DJD

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

NDB RWY 5, AMDT 4

25 AUG 2011

SUP: NDB RWY 4

AMDT: 3A

DATED: 01/15/2009