

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
SPRINGDALE, AR	SPRINGDALE MUNI	18 NOV 2010	5

**TAKEOFF MINIMUMS:**

RWY 18, STANDARD.

RWY 36, 400 – 2 1/2 OR STANDARD WITH MINIMUM CLIMB OF 332 FT PER NM TO 1900.

**TEXTUAL DEPARTURE PROCEDURES:**

RWY 36 – CLIMB HEADING 003.09 TO 2000 BEFORE TURNING.

**TAKEOFF OBSTACLE NOTES:**

**NOTE: RWY 18,** TREES AND POLES BEGINNING 166 FT FROM DER, 242 FT LEFT OF CENTERLINE, UP TO 56 FT AGL/1395 FT MSL. TREES BEGINNING 42 FT FROM DER, 374 FT RIGHT OF CENTERLINE, UP TO 69 FT AGL/1408 FT MSL.

**NOTE: RWY 36,** TREES, TOWER, FENCE, AND ROAD BEGINNING 296 FT FROM DER, 191 FT LEFT OF CENTERLINE, UP TO 44 FT AGL/1404 FT MSL. POLES, TREES, AND BLDG BEGINNING 354 FT FROM DER, 324 FT RIGHT OF CENTERLINE, UP TO 59 FT AGL/1418 FT MSL.

**CONTROLLING OBSTACLES:**

RWY 36: 1681 MSL TOWER 361232.00N/0940624.00W, 1700 FT MSL TREE 361259.87N/0940626.57W.

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 36 – 1812 FT MSL ANTENNA 361233.72N/0940607.45W.

QUALITY  
CHECKED