

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT , HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: 4.53 MILES AFTER ZOTLU OR AT TXO 11.83 DME FIX						
TXO VORTAC (IF/IAF)		ZOTLU/TXO 7.30 DME/RADAR			241.62 / 7.30			5700		CLIMB TO 4700 THEN CLIMBING RIGHT TURN TO 6000 DIRECT TXO VORTAC AND HOLD.						
										ADDITIONAL FLIGHT DATA: CHART FAS OBST: 4345 DERRICK 342716N/1030334W CHART BRONCO 1 MOA. CHART KCVS IN PLANVIEW. CHART VDP AT 10.77 DME DISTANCE VDP TO THLD 1.06 MILES. CHART CIRCLING ICON. ZOTLU TO RW22: 2.99/47.						
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)																
2. HOLD NE TXO VORTAC, RT, 241.62 INBOUND, 6000 FT. IN LIEU OF PT (IAF)																
3. FAC 241.62 FAF ZOTLU/TXO 7.30 DME/RADAR DIST FAF TO MAP 4.53 THLD 4.53																
4. MIN. ALT TXO VORTAC 6000, ZOTLU 5700, WUMGU/TXO 9.33 DME/RADAR 5040																
8. MSA FROM: TXO VORTAC 6100										MAG VAR: 11E					EPOCH YEAR:1965	
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-22		4600	1	386	4600	1	386	4600	1 1/8	386	4600	1 1/8	386			
CIRCLING		4680	1	464	4680	1	464	4700	1 1/2	484	4820	2	604			
NOTES:																
CHART NOTE: DME OR RADAR REQUIRED.																
CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON TXO VORTAC AIRWAY RADIALS 040 CW 125.																
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CANNON AFB ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET; INCREASE S-22 CAT C/D VISIBILITY 1/8 MILE.																
CHART NOTE: VDP NA WHEN USING CANNON AFB ALTIMETER SETTING.																
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.																
CITY AND STATE ELEVATION: 4216 TDZE: 4214 FACILITY IDENTIFIER: PROCEDURE NO./AMDT NO./EFFECTIVE DATE: SUP																
CLOVIS, NM		AIRPORT NAME:			CLOVIS MUNI			TXO			VOR RWY 22, AMDT 5 15 OCTOBER 2015				AMDT 4A	
															DATE 06/12/2004	



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

CLOVIS, NM

ELEVATION: 4216

TDZE: 4214

AIRPORT NAME:

CLOVIS MUNI

FACILITY
IDENTIFIER:

TXO

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 22, AMDT 5

15 OCTOBER 2015

SUP:

AMDT: 4A

DATED: 06/12/2004

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

CLOVIS, NM

ELEVATION: 4216

TDZE: 4214

AIRPORT NAME:

CLOVIS MUNI

FACILITY
IDENTIFIER:

TXO

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 22, AMDT 5

15 OCTOBER 2015

SUP:

AMDT: 4A

DATED: 06/12/2004