

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CANNON AFB ALTIMETER SETTING AND INCREASE ALL DA AND MDA 40 FEET; INCREASE LNAV CAT C/D VISIBILITY 1/4 MILE.

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 3/4 MILE.

CHART NOTE: FOR INOPERATIVE MALSR WHEN USING CANNON AFB ALTIMETER SETTING, INCREASE LNAV CAT C/D VISIBILITY TO 1 3/8 MILE.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING CANNON AFB ALTIMETER SETTING.



CITY AND STATE CLOVIS, NM	ELEVATION: 4216 TDZE: 4205 AIRPORT NAME: CLOVIS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 15 OCTOBER 2015	SUP:
				AMDT: ORIG
				DATED: 09/30/2004

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE
CLOVIS, NM

ELEVATION: 4216 TDZE: 4205
AIRPORT NAME:
CLOVIS MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 4, AMDT 1
15 OCTOBER 2015

SUP:	
AMDT:	ORIG
DATED:	09/30/2004

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCVN
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	342519.5300N
LTP/FTP LONGITUDE	1030503.1600W
LTP/FTP ELLIPSOIDAL HEIGHT	+12545
FPAP LATITUDE	342621.9695N
FPAP LONGITUDE	1030346.1925W
THRESHOLD CROSSING HEIGHT (TCH)	00053.2
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0560
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 21E0D0F3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+12784
FPAP ORTHOMETRIC HEIGHT	+12784

QUALITY
25
CHECKED

CITY AND STATE CLOVIS, NM	ELEVATION: 4216 TDZE: 4205 AIRPORT NAME: CLOVIS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 15 OCTOBER 2015	SUP:
				AMDT: ORIG
				DATED: 09/30/2004


Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible][illegible]

CITY AND STATE CLOVIS, NM	ELEVATION: 4216 TDZE: 4205 AIRPORT NAME: CLOVIS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 15 OCTOBER 2015	SUP:	CHECKED
				AMDT:	ORIG
				DATED:	09/30/2004

QUALITY
25
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	KEBYO	KEBYO	010	IAF	IF		FB					
	KEBYO	VEZFO	020		TF		FB	1.0	306.6 (315.6T)	008.7	AA 06300	
	VEZFO	VEZFO	010	IAF	HF	R	FO		036.5 (045.5T)	007.0	AA 06300	
		VEZFO	010	FACF	IF		FB				AA 06300	
		ELDAJ	020	FAF	TF		FB	0.5	036.5 (045.5T)	006.6	AA 06300	
		CIPAT	021	SDF	TF		FB	0.3	036.6 (045.6T)	003.4	AA 05200	GS 05203
		RW04	030	MAP	TF		FO	0.3	036.6 (045.6T)	003.0	AT 04248	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		036.6 (045.6T)		AA 04405	
		RIMKE	050		DF		FO				AA 06000	
		RIMKE	060		HM	R	FO		216.7 (225.7T)	005.0	AA 06000	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		CIPAT	N342313.35		W1030738.55		N3423.223		W10307.643			
		ELDAJ	N342048.48		W1031036.72		N3420.808		W10310.612			
		KEBYO	N340956.99		W1030855.73		N3409.950		W10308.929			
		RIMKE	N343325.85		W1025502.39		N3433.431		W10255.040			
		VEZFO	N341610.81		W1031617.48		N3416.180		W10316.291			
		RW04	N342519.53		W1030503.16		N3425.326		W10305.053			
RUNWAY DATA		RWY	THRESHOLD ELEVATION		TCH							
		RW04	04194		53							



CITY AND STATE CLOVIS, NM	ELEVATION: 4216	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 15 OCTOBER 2015	SUP:
	AIRPORT NAME: CLOVIS MUNI			AMDT: ORIG
				DATED: 09/30/2004