

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW17					
EKIBE (IAF)		FARPA (NOPT) (FB)		262.44 / 5.00				5200		CLIMB TO 5200 DIRECT NULIC AND HOLD.					
DOBSE (IAF)		FARPA (NOPT) (FB)		082.32 / 5.00				5200							
FARPA (IF/IAF)		CULVA (FB)		172.38 / 6.10				4900		ADDITIONAL FLIGHT DATA: HOLD S, RT, 352.38 INBOUND. CHART FAS OBST: 3459 TREE 373650N/1014445W 3514 AAO 374001N/1014514W. CHART VDP AT 1.12 MILES TO RW17. CULVA TO RW17: 3.04/40. CHART AIRPORT ELEV: 3325					
CULVA (FAF)		OZUMO/1.80 NM TO RW17 (FB)		172.38 / 2.96											
OZUMO/1.80 NM TO RW17		RW17 (MAP) (FO)		172.38 / 1.80											
RW17 (MAP)		3720 MSL		172.38											
3720 MSL		NULIC (FO)						5200							

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)									
2. HOLD N FARPA, RT, 172.38 INBOUND, 5200 FT. IN LIEU OF PT (IAF)									
3. FAC: <u>172.38</u> FAF: <u>CULVA</u> DIST FAF TO MAP: <u>4.76</u> THLD: <u>4.76</u>									
4. MIN. ALT: FARPA 5200, CULVA 4900, OZUMO/1.80 NM TO RW17 3940									
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>									
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>									
7. GS ANGLE: <u> </u> TCH: 34:1 IS CLEAR									
8. MSA FROM: <u> </u>									

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X					
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	3720	1	396	3720	1	396	3720	1	396	3720	1 1/4	396			
CIRCLING	3760	1	435	3840	1	515	3840	1 1/2	515	3880	2	555			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LIBERAL ALTIMETER SETTING AND INCREASE ALL MDA 180 FEET. INCREASE LNAV CAT C/D VISIBILITY 1/2 MILE, CIRCLING CAT C VISIBILITY 1/2 MILE (SEE FORM 8260-10)

CITY AND STATE JOHNSON, KS		ELEVATION: 3325 TDZE: 3324 AIRPORT NAME: STANTON COUNTY MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 1 18 NOV 2010		SUP: AMDT: ORIG DATED 07/05/2007	
-------------------------------	--	--	--	------------------------------	--	--	--	--	--

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

AND CIRCLING CAT D 1/4 MILE.

CHART NOTE: VDP NA WITH LIBERAL ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	082/30 CW 262/30 (NOPT)	082/13 CW 262/13	5600
2.	082/13 CW 262/13	FARPA (IF/IAF) (FB)	5200
3.	262/30 CW 352/30	EKIBE (IAF) (FB)	5200
4.	352/30 CW 082/30	352/13 CW 082/13	5700
5.	352/13 CW 082/13	DOBSE (IAF) (FB)	5300

QUALITY
2
CHECKED

CITY AND STATE

JOHNSON, KS

ELEVATION: 3325

TDZE: 3324

AIRPORT NAME:

STANTON COUNTY MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, AMDT 1

18 NOV 2010

SUP:

AMDT:

ORIG

DATED:

07/05/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 2K3 K3FR17	ADOBSE	010DOBSEK3EA0E	A	IF					18000			B	JS
SUSAP 2K3 K3FR17	ADOBSE	020FARPAK3EA0EE	B	010TF		08230050	+	05200				B	JS
SUSAP 2K3 K3FR17	AEKIBE	010EKIBEK3EA0E	A	IF					18000			B	JS
SUSAP 2K3 K3FR17	AEKIBE	020FARPAK3EA0EE	B	010TF		26240050	+	05200				B	JS
SUSAP 2K3 K3FR17	AFARPA	010FARPAK3EA0EE	AR	HF		17240050	+	05200		18000		B	JS
SUSAP 2K3 K3FR17	R	010FARPAK3EA0E	I	IF			+	05200		18000		B	JS
SUSAP 2K3 K3FR17	R	020CULVAK3EA1E	F	051TF		17240061	+	04900				B	JS
SUSAP 2K3 K3FR17	R	020CULVAK3EA2WN			N	ALNAV							JS
SUSAP 2K3 K3FR17	R	021OZUMOK3EA0E	S	031TF		17240030	V	0394003948		-304		B	JS
SUSAP 2K3 K3FR17	R	030RW17 K3PGOGY	M	031TF		17240018		03364		-304		B	JS
SUSAP 2K3 K3FR17	R	040	0	M 010CA		1724	+	03720				B	JS
SUSAP 2K3 K3FR17	R	050NULICK3EA0EY		010DF				+	05200			B	JS
SUSAP 2K3 K3FR17	R	060NULICK3EA0EE		R020HM		35240050	+	05200				B	JS

[illegible]

QUALITY
4
CHECKED

CITY AND STATE
JOHNSON, KS

ELEVATION: 3325 TDZE: 3324
AIRPORT NAME:
STANTON COUNTY MUNI

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 17, AMDT 1
18 NOV 2010

SUP:	
AMDT:	ORIG
DATED:	07/05/2007