

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW27 CLIMB TO 6000 DIRECT CIVKU AND ON TRACK 247.51 TO DORIA AND HOLD, CONTINUE CLIMB-IN-HOLD TO 6000. ADDITIONAL FLIGHT DATA: HOLD W, RT, 071.65 INBOUND. CHART FAS OBST: 2239 TREE 480804N/1050634W CHART WOLF POINT ASOS. QUMGY TO RW27: 3.04/40.
DORIA	DAXIQ (FO)	079.74 / 27.23	4500	
RILMY (IAF)	DAXIQ (NOPT) (FB)	184.92 / 4.24	4500	
DAXIQ (IF/IAF)	LITVE (FB)	274.66 / 4.10	3900	
LITVE	QUMGY (FB)	274.59 / 2.00	3600	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E DAXIQ, RT, 274.66 INBOUND, 4500 FT. IN LIEU OF PT (IAF)
- FAC: 274.55 FAF: QUMGY DIST FAF TO MAP: 4.72 THLD: 4.72
- MIN. ALT: DAXIQ 4500, LITVE 3900, QUMGY 3600, FOKBU/2.50 NM TO RW27 2860
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW27 4200

MAG VAR: 10E

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X											
CATEGORY	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	2540	1	506	2540	1	506		NA			NA					
CIRCLING	2560	1	524	2600	1	564		NA			NA					

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGS/ AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: USE WOLF POINT ALTIMETER SETTING; WHEN NOT RECEIVED USE SIDNEY ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET.

CITY AND STATE	ELEVATION: 2036 TDZE: 2034	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG 23 SEP 2010	SUP: AMDT: DATED
POPLAR, MT	AIRPORT NAME: POPLAR MUNI			NONE

QUALITY
2
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

WP	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAEENRT	CIVKU	K10	W	N48082613W105123323				E0100	NAR		CIVKU		
SUSAEENRT	DAXIQ	K10	W	N48051004W104534481				E0098	NAR		DAXIQ		
SUSAEENRT	DORIA	K10	C	L N48050986W105342179				E0102	NAR		DORIA		
SUSAEENRT	FOKBU	K10	W	N48071570W105054561				E0099	NAR		FOKBU		
SUSAEENRT	LITVE	K10	W	N48061205W104593952				E0098	NAR		LITVE		
SUSAEENRT	QUMGY	K10	W	N48064223W105023282				E0099	NAR		QUMGY		
SUSAEENRT	RILMY	K10	C	L N48091545W104520719				E0098	NAR		RILMY		

[illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE POPLAR, MT	ELEVATION: 2036 TDZE: 2034 AIRPORT NAME: POPLAR MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
			RNAV (GPS) RWY 27, ORIG	AMDT: NONE
			23 SEP 2010	DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

Q. A
CHECKED

CITY AND STATE POPLAR, MT	ELEVATION: 2036 TDZE: 2034 AIRPORT NAME: POPLAR MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG 23 SEP 2010	SUP:
				AMDT: NONE
				DATED: