

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW13 CLIMB TO 3000 DIRECT WAGUS AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, LT, 310.81 INBOUND. CHART FAS OBST: 890 TREE 330133N/0850545W DISTANCE TO THLD FROM 401 HAT: 1.10 NM. CHART VDP AT 1.10 MILES TO RW13* *LNAV ONLY. WAAS CHANNEL # 40416 REFERENCE PATH ID: W13A											
TIMMY	COVOL (FB)	038.00 / 19.20	4000												
TIROE	OHOPA (FB)	254.09 / 18.60	4000												
COVOL (IAF)	WERTU (NOPT) (FB)	040.56 / 5.00	3500												
OHOPA (IAF)	WERTU (NOPT) (FB)	220.62 / 5.00	3500												
WERTU (IF/IAF)	OSDOW (FB)	130.59 / 7.00	2400												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW WERTU, RT, 130.59 INBOUND, 3500 FT. IN LIEU OF PT (IAF) 3. FAC: <u>130.65</u> FAF: <u>OSDOW</u> DIST FAF TO MAP: <u>5.16</u> THLD: <u>5.16</u> 4. MIN. ALT: WERTU 3500, OSDOW 2400 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>2400</u> GS ALT AT: <u>OSDOW 2400</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>52.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: RW13 3500				MAG VAR: 4W EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY ==>	A		B		C	D	E								
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1082	1 1/2	401	1082	1 1/2	401	1082	1 1/2	401	1082	1 1/2	401			
LNAV/VNAV DA	1212	1 3/4	531	1212	1 3/4	531	1212	1 3/4	531	1212	1 3/4	531			
LNAV MDA	1140	1	459	1140	1	459	1140	1 1/4	459	1140	1 1/2	459			
CIRCLING	1280	1	586	1280	1	586	1280	1 1/2	586	1280	2	586			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. SEE 8260-10															
CITY AND STATE		ELEVATION: 694 TDZE: 681		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
LAGRANGE, GA		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 13, ORIG-A				AMDT: ORIG					
		LAGRANGE-CALLAWAY				03 JUN 2010				DATED 04/08/2010					



**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: VDP AND BARO-VNAV NA WHEN USING COLUMBUS ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT TIROE ON V222 NORTHEAST BOUND, AND FOR ARRIVALS AT TIMMY ON V222 SOUTHWEST BOUND.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLUMBUS ALTIMETER SETTING AND INCREASE ALL DA 112 FEET AND ALL MDA 120 FEET, INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 1/2 MILE, LNAV CAT C AND D VISIBILITY 1/4 MILE, CIRCLING CAT C VISIBILITY 1/2 MILE, AND CAT D VISIBILITY 1/4 MILE.

QUALITY
4
CHECKED

CITY AND STATE

LAGRANGE, GA

ELEVATION: 694 TDZE: 881

AIRPORT NAME:

LAGRANGE-CALLAWAY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, ORIG-A

03 JUN 2010

SUP:

AMDT: ORIG

DATED: 04/08/2010

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KLGC
RUNWAY RW13
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W13A
LTP/FTP LATITUDE 330042.9525N
LTP/FTP LONGITUDE 0850444.9810W
LTP/FTP ELLIPSOIDAL HEIGHT +01783
FPAP LATITUDE 325949.5900N
FPAP LONGITUDE 0850320.0400W
THRESHOLD CROSSING HEIGHT (TCH) 00052.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1040
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

957E6166

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K7
LTP ORTHOMETRIC HEIGHT +02074
FPAP ORTHOMETRIC HEIGHT +02074

QUALITY
4
CHECKED

CITY AND STATE LAGRANGE, GA	ELEVATION: 694 TDZE: 681 AIRPORT NAME: LAGRANGE-CALLAWAY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG-A 03 JUN 2010	SUP:
				AMDT: ORIG
				DATED: 04/08/2010

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KLGCK7FR13	ATIMMY	010TIMMYK7EA0E	IF							18000		A JS	
SUSAP KLGCK7FR13	ATIMMY	020COVOLK7EA0E	A 020TF			03800192		+ 04000				A JS	
SUSAP KLGCK7FR13	ATIMMY	030WERTUK7EA0EE	B 010TF			04060050		+ 03500				A JS	
SUSAP KLGCK7FR13	ATIROE	010TIROEK7EA0E	IF							18000		A JS	
SUSAP KLGCK7FR13	ATIROE	020OHOPAK7EA0E	A 020TF			25410186		+ 04000				A JS	
SUSAP KLGCK7FR13	ATIROE	030WERTUK7EA0EE	B 010TF			22060050		+ 03500				A JS	
SUSAP KLGCK7FR13	AWERTU	010WERTUK7EA0EE	AR HF			13060040		+ 03500		18000		A JS	
SUSAP KLGCK7FR13	R	010WERTUK7EA0E	I IF					+ 03500		18000		A JS	
SUSAP KLGCK7FR13	R	020OSDOWK7EA1E	F 051TF			13060070		+ 02400			RW13	K7PGA JS	
SUSAP KLGCK7FR13	R	020OSDOWK7EA2WALPV		ALNAV/VNAV	ALNAV							JS	
SUSAP KLGCK7FR13	R	030RW13 K7PG0GY	M 031TF			13070052		00733		-300		A JS	
SUSAP KLGCK7FR13	R	040	0 M 010CA			1307		+ 01082				A JS	
SUSAP KLGCK7FR13	R	050WAGUSK7EA0EY	010DF					+ 03000				A JS	
SUSAP KLGCK7FR13	R	060WAGUSK7EA0EE	L020HM			31080040		+ 03000				A JS	

[illegible]

QUALITY
4
CHECKED

CITY AND STATE LAGRANGE, GA	ELEVATION: 694 TDZE: 681 AIRPORT NAME: LAGRANGE-CALLAWAY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG-A 03 JUN 2010	SUP:
				AMDT: ORIG
				DATED: 04/08/2010

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

4
CHECKED

SUP:	
AMDT:	ORIG
DATED:	04/08/2010