

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
MOBRIDGE, SD	MOBRIDGE MUNI	30 JUN 2011	1

TAKEOFF MINIMUMS:

RWY 12, 30: STANDARD.

RWY 35, 17, NA- ENVIRONMENTAL

TEXTUAL DEPARTURE PROCEDURES:

RWY 12: CLIMB HEADING 117.69 TO 2600 BEFORE TURNING LEFT.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 12, TOWER 2587 FT FROM DER, 651 FT RIGHT OF CENTERLINE, 40 FT AGL/ 1810 FT MSL. POLE 3567 FT FROM DER, 12 FT RIGHT OF CENTERLINE, 11 FT AGL/ 1790 FT MSL. TREE 1495 FT FROM DER, 230 FT RIGHT OF CENTERLINE, 29 FT AGL/ 1738 FT MSL. TREES AND POLES BEGINNING 1698 FT FROM DER, 160 FT LEFT OF CENTERLINE, UP TO 75 FT AGL/ 1811 FT MSL. TERRAIN AND ROAD BEGINNING 153 FT FROM DER, 307 FT LEFT OF CENTERLINE, UP TO 17FT AGL/1749 FT MSL.

NOTE: RWY 30, TERRAIN AND ROAD BEGINNING 36 FT FROM DER, LEFT TO RIGHT ACROSS CENTERLINE, UP TO 17 FT AGL/1710 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 12- 2395 FT MSL TOWER 453207.00N/1002046.00W

