

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV: RW34 (DO NOT EXCEED 165 KIAS UNTIL GLUGS) CLIMB TO 3400, THEN CLIMBING RIGHT TURN TO 5000 DIRECT GLUGS AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 2975 ANTENNA 431348N/1005038W DISTANCE TO THLD FROM 359 HAT: 1.00 NM. WAAS CHANNEL # 69241 REFERENCE PATH ID: W34A CHART CIRCLING ICON. LTP HAE: 807.9 M									
GLUGS (IF/IAF)		ROLFS (TF) (FB) (RNP 1.00)		343.66 / 6.00				4200											
ROLFS (FAF)		RW34 (MAP) (TF) (FO) (RNP 0.30)		343.64 / 4.51															
RW34 (MAP)		3400 MSL (CA)		343.64				3400											
3400 MSL		GLUGS (DF) (FO) (RNP 1.00)						5000											
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S GLUGS, RT, 343.66 INBOUND, 5000 FT. IN LIEU OF PT (IAF) 3. FAC: 343.64 FAF: ROLFS DIST FAF TO MAP: 4.51 THLD: 4.51 4. MIN. ALT: GLUGS 5000, ROLFS 4200 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 4200 GS ALT AT: ROLFS 4200 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 39.7 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 6E		EPOCH YEAR: 2020	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		<input checked="" type="checkbox"/>									
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	3083	1 1/4	359	3083	1 1/4	359	3083	1 1/4	359		NA								
LNAV MDA	3320	1	596	3320	1	596	3320	1 3/4	596		NA								
CIRCLING	3340	1	616	3360	1	636	3440	2	716		NA								
NOTES: CHART NOTE: RWY 34 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: USE VALENTINE ALTIMETER SETTING, WHEN NOT RECEIVED PROCEDURE NA.																			
CITY AND STATE		ELEVATION: 2724 TDZE: 2724				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:							
ROSEBUD, SD		AIRPORT NAME: ROSEBUD SIOUX TRIBAL						RNAV (GPS) RWY 34, ORIG 7 DECEMBER 2017				AMDT: NONE							
												DATED							

QUALITY
5
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	254/30 CW 074/30 (NOPT)	GLUGS (IF/IAF) (FB)	5000
2.	074/30 CW 254/30	GLUGS (IF/IAF) (FO)	5000

QUALITY
5
CHECKED

CITY AND STATE

ROSEBUD, SD

ELEVATION: 2724

TDZE: 2724

AIRPORT NAME:

ROSEBUD SIOUX TRIBAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 34, ORIG

7 DECEMBER 2017

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSUO
RUNWAY	RW34
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W34A
LTP/FTP LATITUDE	431507.1255N
LTP/FTP LONGITUDE	1005128.3405W
LTP/FTP ELLIPSOIDAL HEIGHT	+08079
FPAP LATITUDE	431634.7865N
FPAP LONGITUDE	1005150.2950W
THRESHOLD CROSSING HEIGHT (TCH)	00039.7
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1288
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 2B67BBDA

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+08303
FPAP ORTHOMETRIC HEIGHT	+08303

QUALITY
5
CHECKED

CITY AND STATE ROSEBUD, SD	ELEVATION: 2724 AIRPORT NAME: ROSEBUD SIOUX TRIBAL	TDZE: 2724	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 7 DECEMBER 2017	SUP:
					AMDT: NONE
					DATED: