

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION TACAN STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: BUMKE/FOE 0.79 DME FIX						
TOP VORTAC		PONDR/FOE 11.00 DME			164.79 / 18.60			3000		CLIMBING LEFT TURN TO 3000 HEADING 190 AND ON FOE TACAN R-213 TO STANC/19.00 DME AND HOLD.						
PONDR/FOE 11.00 DME (IF/IAF)		IFONA/FOE 5.00 DME			304.00 / 6.00 (FOE R-124)			2500								
										ADDITIONAL FLIGHT DATA: HOLD NE, RT, 213.00 INBOUND. CHART IN PLANVIEW: MAXIMUM HOLDING AIRSPEED 230 KIAS. FAS OBST: 1250 AAO 385504N/0953437W 1260 AAO 385333N/0953404W CHART VDP AT 2.06 DME DISTANCE VDP TO THLD 1.27 NM. IFONA TO RW31: 3.15/58. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 2405 FT FROM THLD.						
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 5E EPOCH YEAR: 1990						
2. HOLD SE PONDR, LT, 304.00 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC 304.00 FAF IFONA/FOE 5.00 DME DIST FAF TO MAP _____ THLD 4.21																
4. MIN. ALT PONDR 3000, IFONA 2500																
8. MSA FROM: FOE TACAN 360-180 3100, 180-360 3600, ESA W/IN 100 NM 3600																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-31	1500	2400	463	1500	2400	463	1500	5000	463	1500	5000	463	1500	5000	463	
CIRCLING	1520	1	442	1580	1	502	1580	1 1/2	502	1700	2	622	1720	2 1/4	642	
NOTES: CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-31 CAT C/D/E VISIBILITY TO 1 3/8 SM. CHART IN PLANVIEW: NOT FOR CIVIL USE.																
CITY AND STATE TOPEKA, KS		ELEVATION: 1078 TDZE: 1037 AIRPORT NAME: TOPEKA RGNL		FACILITY IDENTIFIER: FOE		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: TACAN RWY 31, AMDT 4A 5 JANUARY 2017				SUP AMD'T DATE		10 4 07/02/2009				