

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 8.03 MILES AFTER PSB VORTAC OR AT MADIW/ 8.03 DME FIX CLIMBING LEFT TURN TO 4000 DIRECT PSB VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 2091 TOWER 405335N/0775147W CHART: 2855 TOWER 405514N/0775827W FAC CROSSES MID POINT OF RWY 07-25. CHART CIRCLING ICON CHART STATE COLLEGE AWOS-3. CHART UNIVERSITY PARK AIRPORT.									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW PSB VORTAC, LT, 112.87 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC <u>112.87</u> FAF PSB VORTAC <u> </u> DIST FAF TO MAP <u>8.03</u> THLD <u> </u> 4. MIN. ALT PSB VORTAC 4000, BAIER/PSB 5.60 DME 2920* 8. MSA FROM: PSB VORTAC 4200																MAG VAR: 10W		EPOCH YEAR: 1985	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A <input type="checkbox"/> X <input type="checkbox"/>											
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
CIRCLING		2920	1 1/4	1848	2920	1 1/2	1848		NA			NA							
BAIER FIX MINIMUMS (DME REQUIRED)																			
CIRCLING		2360	1 1/4	1288	2380	1 1/2	1308		NA			NA							
NOTES:																			
CHART NOTE: CIRCLING TO RWY 07 NA AT NIGHT. *3060 WHEN USING CLEARFIELD ALTIMETER SETTING. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: USE STATE COLLEGE ALTIMETER SETTING, WHEN NOT RECEIVED USE CLEARFIELD ALTIMETER (SEE FORM 8260-10)																			
CITY AND STATE				ELEVATION: 1072		TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR OR GPS-A					
BELLEFONTE, PA				AIRPORT NAME:		BELLEFONTE		PSB		VOR-A, AMDT 2 19 SEPTEMBER 2013				AMDT 1B					
													DATE 03/11/2010						

QUALITY
1
CHECKED

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

SETTING AND INCREASE ALL MDA 140FT.

CHART NOTE: CIRCLING NA SOUTHEAST OF RWY 7-25.

CITY AND STATE
BELLEFONTE, PAELEVATION: 1072 TDZE:
AIRPORT NAME:
BELLEFONTEFACILITY
IDENTIFIER:
PSBPROCEDURE NO./AMDT NO./EFFECTIVE DATE:
VOR-A, AMDT 2
19 SEPTEMBER 2013SUP: VOR OR GPS-A
AMDT: 1B
DATED: 03/11/2010