

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
ROCKWOOD, TN	ROCKWOOD MUNI	15 DEC 2011	2

**TAKEOFF MINIMUMS:**

RWY 4, 22: STANDARD.

**TEXTUAL DEPARTURE PROCEDURES:**

NOTE: RWY 4, CLIMB HEADING 044.21 TO 2500 BEFORE TURNING LEFT.

NOTE: RWY 22, CLIMB HEADING 224.22 TO 2600 BEFORE PROCEEDING ON COURSE.

**TAKEOFF OBSTACLE NOTES:**

NOTE: RWY 4, TREES BEGINNING 100 FT FROM DER, 234 FT RIGHT OF CENTERLINE, UP TO 81 FT AGL/1646 FT MSL. TREES BEGINNING 593 FT FROM DER, 557 FT LEFT OF CENTERLINE, UP TO 88 FT AGL/1649 FT MSL.

NOTE: RWY 22, TREES BEGINNING 54 FT FROM DER, 101 FT LEFT OF CENTERLINE, UP TO 71 FT AGL/1676 FT MSL. TREES BEGINNING 630 FT FROM DER, 136 FT RIGHT OF CENTERLINE, UP TO 70 FT AGL/1691 FT MSL.

**CONTROLLING OBSTACLES:**

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 4 - 2719 FT MSL AAO 355921.43N/0844332.07W. RWY 22 - 2959 FT MSL AAO 355712.94N/0844712.75W.

QUALITY  
2  
CHECKED