

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW19						
HODEN		FALIS (FO)		050.95 / 14.12				3000		CLIMB TO 3000 DIRECT BEJCY AND HOLD.						
OCTAM (IAF)		FALIS (NOPT) (FB)		167.78 / 5.98				3000								
FALIS (IF/IAF)		JIDIR (FB)		187.13 / 5.92				2500		ADDITIONAL FLIGHT DATA: HOLD S, RT, 007.09 INBOUND. CHART FAS OBST: 842 TREE 384734N/0934812W DISTANCE TO THLD FROM 250 HAT: 0.66 NM. WAAS CHANNEL # 45803 REFERENCE PATH ID: W19A CHART CIRCLING ICON. LTP HAE: 209.8 M						
JIDIR (FAF)		ZEVNI/1.70 NM TO RW19 (FB)		187.12 / 3.53												
ZEVNI/1.70 NM TO RW19		RW19 (MAP) (FO)		187.12 / 1.70												
RW19 (MAP)		1047 MSL		187.12												
1047 MSL		BEJCY (FO)						3000								
1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)										MAG VAR: 1E EPOCH YEAR: 2015						
2. HOLD N FALIS, RT, 187.13 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC: 187.12 FAF: JIDIR DIST FAF TO MAP: 5.23 THLD: 5.23																
4. MIN. ALT: FALIS 3000, JIDIR 2500, ZEVNI/1.70 NM TO RW19 1360*																
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____																
6. MIN GS INCPT: 2500 GS ALT AT: JIDIR 2500 OM: ____ MM: ____ IM: ____																
7. GS ANGLE: 3.00 TCH: 40.1 34:1 IS CLEAR																
8. MSA FROM: RW19 3100																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1047	1	250	1047	1	250	1047	1	250		NA					
LNAV/VNAV DA	1102	1	305	1102	1	305	1102	1	305		NA					
LNAV MDA	1240	1	443	1240	1	443	1240	1 3/8	443		NA					
CIRCLING	1260	1	462	1340	1	542	1380	1 1/2	582		NA					
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING WHITEMAN AFB ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HODEN ON V159 SOUTHEAST BOUND. (SEE FORM 8260-10)																
CITY AND STATE WARRENSBURG, MO		ELEVATION: 798 TDZE: 797 AIRPORT NAME: SKYHAVEN		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 30 APRIL 2015					SUP: RNAV (GPS) RWY 19 AMDT: 10 ORIG-B DATED: 02/31/2008					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
NOTES, (CONT.): CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT OCTAM ON V12 WESTBOUND. *RNAV ONLY CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WHITEMAN AFB ALTIMETER SETTING AND INCREASE ALL DA 39 FEET AND ALL MDA 40 FEET; INCREASE RNAV/VNAV ALL CATS VISIBILITY 1/8 MILE, AND INCREASE CAT C CIRCLING VISIBILITY 1/4 MILE.				
CITY AND STATE WARRENSBURG, MO	ELEVATION: 798 AIRPORT NAME: SKYHAVEN	TDZE: 797	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 30 APRIL 2015
				SUP: RNAV (GPS) RWY 18 AMDT: 10 ORIG-B DATED: 07/31/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KRCM
RUNWAY RW19
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W19A
LTP/FTP LATITUDE 384730.6780N
LTP/FTP LONGITUDE 0934805.1070W
LTP/FTP ELLIPSOIDAL HEIGHT +02098
FPAP LATITUDE 384602.3800N
FPAP LONGITUDE 0934821.1800W
THRESHOLD CROSSING HEIGHT (TCH) 00040.1
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1472
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

CFCD882A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K3
LTP ORTHOMETRIC HEIGHT +02425
FPAP ORTHOMETRIC HEIGHT +02425

CITY AND STATE

WARRENSBURG, MO

ELEVATION: 798

TDZE: 797

AIRPORT NAME:

SKYHAVEN

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, AMDT 1

30 APRIL 2015

SUP: RNAV (GPS) RWY 18

AMDT: 10 ORIG-B

DATED: 07/31/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE WARRENSBURG, MO	ELEVATION: 798	TDZE: 797	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 30 APRIL 2015	SUP: RNAV (GPS) RWY 18
	AIRPORT NAME: SKYHAVEN				AMDT: 10 ORIG-B
					DATED: 07/31/2008

<p align="center">U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</p> <p align="center"><u>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</u></p> <p align="center">FLIGHT STANDARDS SERVICES - FAR PART 97.33</p>	<p>Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.</p>
--	---

<p align="center">U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</p> <p align="center"><u>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</u></p> <p align="center">FLIGHT STANDARDS SERVICES - FAR PART 97.33</p>	<p>Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.</p>
--	---

[illegible]

CITY AND STATE
WARRENSBURG, MO

ELEVATION: 798	TDZE: 797
AIRPORT NAME:	SKYHAVEN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 19, AMDT 1
 30 APRIL 2015

SUP:	RNAV (GPS) RWY 18
AMDT:	10 ORIG-B
DATED:	07/31/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - FAR PART 97.33								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	HODEN	HODEN	010		IF		FB					
	HODEN	FALIS	020		TF		FO	2.0	051.0 (052.0T)	014.1	AA 03000	
	HODEN	FALIS	030	IAF	HF	R	FO		187.1 (188.1T)	004.0	AA 03000	
	OCTAM	OCTAM	010	IAF	IF		FB					
	OCTAM	FALIS	020		TF		FB	1.0	167.8 (168.8T)	006.0	AA 03000	
		FALIS	010	FACF	IF		FB				AA 03000	
		JIDIR	020	FAF	TF		FB	0.5	187.1 (188.1T)	005.9	AA 02500	
		ZEVNI	021	SDF	TF		FB	0.3	187.1 (188.1T)	003.5	AA 01360	GS 01377
		RW19	030	MAP	TF		FO	0.3	187.1 (188.1T)	001.7	AT 00836	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		187.1 (188.1T)		AA 01047	
		BEJCY	050		DF		FO				AA 03000	
		BEJCY	060		HM	R	FO		007.1 (008.1T)	004.0	AA 03000	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		BEJCY	N383544.60		W0935013.33		N3835.743		W09350.222			
		FALIS	N385833.61		W0934604.09		N3858.560		W09346.068			
		HODEN	N384951.81		W0940019.43		N3849.864		W09400.324			
		JIDIR	N385241.40		W0934708.46		N3852.690		W09347.141			
		OCTAM	N390426.08		W0934733.69		N3904.435		W09347.562			
		ZEVNI	N384911.76		W0934746.70		N3849.196		W09347.778			
		RW19	N384730.68		W0934805.11		N3847.511		W09348.085			
RUNWAY DATA			THRESHOLD									
		RWY	ELEVATION		TCH							
		RW19	00796		40							

CITY AND STATE WARRENSBURG, MO	ELEVATION: 798 AIRPORT NAME: SKYHAVEN	TDZE: 797	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 30 APRIL 2015	SUP: RNAV (GPS) RWY 18 AMDT: 10 ORIG-B DATED: 07/31/2008