

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW19						
JOVES (IF/IAF)		BUNYA (FB)		192.44 / 7.00				1900		CLIMB TO 1900 DIRECT NEONS AND HOLD.						
BUNYA (FAF)		PYINS/1.90 NM TO RW19 (FB)		192.42 / 3.20												
PYINS/1.90 NM TO RW19		RW19 (MAP) (FO)		192.42 / 1.90												
RW19 (MAP)		590 MSL		192.42												
590 MSL		NEONS (FO)						1900		ADDITIONAL FLIGHT DATA: HOLD S, RT, 012.39 INBOUND. CHART FAS OBST: 382 TRMSN TWR 342125N/0922109W CHART PINE BLUFF ASOS. DISTANCE TO THLD FROM 354 HAT: 0.98 NM. WAAS CHANNEL # 63237 REFERENCE PATH ID: W19A CHART CIRCLING ICON. LTP HAE: 45.9 M						
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 0E EPOCH YEAR: 2020						
2. HOLD N JOVES, RT, 192.44 INBOUND, 2100 FT. IN LIEU OF PT (IAF)																
3. FAC: 192.42 FAF: BUNYA DIST FAF TO MAP: 5.10 THLD: 5.10																
4. MIN. ALT: JOVES 2100, BUNYA 1900, PYINS/1.90 NM TO RW19 880*																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: 1900 GS ALT AT: BUNYA 1900 OM: _____ MM: _____ IM: _____																
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR																
8. MSA FROM: _____																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	590	1 1/4	354	590	1 1/4	354	590	1 1/4	354		NA					
LNAV/VNAV DA	682	1 1/2	446	682	1 1/2	446	682	1 1/2	446		NA					
LNAV MDA	700	1	464	700	1	464	700	1 3/8	464		NA					
CIRCLING	740	1	504	840	1	604	960	2	724		NA					
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: DME/DME RNP-0.3 NA. *LNAV ONLY CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. (SEE FORM 8260-10)																
CITY AND STATE		ELEVATION: 236 TDZE: 236			AIRPORT NAME:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
SHERIDAN, AR					SHERIDAN MUNI		RNAV		RNAV (GPS) RWY 19, ORIG 10 DECEMBER 2015				AMDT: 10 NONE			
													DATED			

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: NIGHT LANDING: RWY 1 NA.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: USE PINE BLUFF ALTIMETER SETTING, WHEN NOT RECEIVED, USE LITTLE ROCK ALTIMETER SETTING
AND INCREASE ALL DA 5 FEET AND ALL MDA 20 FEET: INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	102/30 CW 282/30 (NOPT)	102/10 CW 282/10	3300
2.	102/10 CW 282/10	JOVES (IF/IAF) (FB)	2100
3.	282/30 CW 102/30	282/4 CW 102/4	3300
4.	282/4 CW 102/4	JOVES (IF/IAF) (FO)	2100

CITY AND STATE

SHERIDAN, AR

ELEVATION: 236**TDZE:** 236**AIRPORT NAME:**

SHERIDAN MUNI

**FACILITY
IDENTIFIER:**

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, ORIG

10 DECEMBER 2015

SUP:**AMDT:** 10 NONE**DATED:**

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	9M8
RUNWAY	RW19
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W19A
LTP/FTP LATITUDE	341954.5555N
LTP/FTP LONGITUDE	0922100.6605W
LTP/FTP ELLIPSOIDAL HEIGHT	+00459
FPAP LATITUDE	341827.3870N
FPAP LONGITUDE	0922123.7755W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1776
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 DAF06401

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00719
FPAP ORTHOMETRIC HEIGHT	+00719

CITY AND STATE SHERIDAN, AR	ELEVATION: 236	TDZE: 236	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 10 DECEMBER 2015	SUP	
	AIRPORT NAME:				AMDT: 10	NONE
	SHERIDAN MUNI				DATED	

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 9M8 K4FR19	AJOVES	010JOVESK4EA0EE	AR	HF			19240040	+	02100	18000		A	JS
SUSAP 9M8 K4FR19	R	010JOVESK4EA0E	I	IF				+	02100	18000		A	JS
SUSAP 9M8 K4FR19	R	020BUNYAK4EA1E	F	051TF			19240070	+	01900			A	JS
SUSAP 9M8 K4FR19	R	020BUNYAK4EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP 9M8 K4FR19	R	021PYINSK4EA0E	S	031TF			19240032	V	0088000881		-300	A	JS
SUSAP 9M8 K4FR19	R	030RW19 K4PGOGY	M	031TF			19240019		00276		-300	A	JS
SUSAP 9M8 K4FR19	R	040	O	M	CA		1924	+	00590			A	JS
SUSAP 9M8 K4FR19	R	050NEONSK4EA0EY		DF				+	01900			A	JS
SUSAP 9M8 K4FR19	R	060NEONSK4EA0EE	R	HM			01240040	+	01900			A	JS

[illegible][illegible]

CITY AND STATE SHERIDAN, AR	ELEVATION: 236 AIRPORT NAME: SHERIDAN MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 10 DECEMBER 2015	SUP: 4
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	JOVES	JOVES	010	IAF	HF	R	FO		192.4 (192.4T)	004.0	AA 02100	
		JOVES	010	FACF	IF		FB				AA 02100	
		BUNYA	020	FAF	TF		FB	0.5	192.4 (192.4T)	007.0	AA 01900	
		PYINS	021	SDF	TF		FB	0.3	192.4 (192.4T)	003.2	AA 00880	GS 00881
		RW19	030	MAP	TF		FO	0.3	192.4 (192.4T)	001.9	AT 00276	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		192.4 (192.4T)		AA 00590	
		NEONS	050		DF		FO				AA 01900	
		NEONS	060		HM	R	FO		012.4 (012.4T)	004.0	AA 01900	
POINT DATA		WAYPOINT			LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS	
		BUNYA			N342453.89		W0921941.18		N3424.898		W09219.686	
		JOVES			N343144.75		W0921751.83		N3431.746		W09217.864	
		NEONS			N340929.35		W0922346.16		N3409.489		W09223.769	
		PYINS			N342146.08		W0922031.07		N3421.768		W09220.518	
		RW19			N341954.56		W0922100.66		N3419.909		W09221.011	
RUNWAY DATA		RWY		THRESHOLD ELEVATION		TCH						
		RW19		00236		40						

CITY AND STATE SHERIDAN, AR	ELEVATION: 236	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 19, ORIG 10 DECEMBER 2015	SUP: QUALITY
	AIRPORT NAME: SHERIDAN MUNI			AMDT: 4 NONE
				DATED: