

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 9 STANDARD.

RWY 18, STANDARD WITH MINIMUM CLIMB OF 284 FEET PER NM TO 2100, OR 1300-3 FOR CLIMB IN VISUAL CONDITIONS.

RWY 27, STANDARD WITH MINIMUM CLIMB OF 300 FEET PER NM TO 2100, OR 1300-2 1/2 FOR CLIMB IN VISUAL CONDITIONS.

RWY 36, STANDARD WITH MINIMUM CLIMB OF 263 FEET PER NM TO 1500, OR 1300-3 FOR CLIMB IN VISUAL CONDITIONS.

(2) DEPARTURE PROCEDURE:

RWY 18, 27, 36 - FOR CLIMB IN VISUAL CONDITIONS: CROSS MARSHALL MEMORIAL MUNICIPAL AIRPORT AT OR ABOVE 1900 MSL BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 36, TOWER 319 FEET FROM DER, 483 FEET RIGHT OF CENTERLINE, 53 FEET AGL/817 FEET MSL. TOWER 1.9 NM FROM DER, 1.1 NM LEFT OF CENTERLINE, 382 FEET AGL/1162 FEET MSL.

(4) CONTROLLING OBSTACLES:

RWY 18: 1737 MSL TOWER 390313.00/0931601.00.

RWY 27: 1737 MSL TOWER 390313.00/0931601.00.

RWY 36: 817 MSL TOWER 390610.00/0931155.00. 1162 MSL ANTENNA 390804.00/0931322.00. 1298 MSL TOWER 390844.96/0931114.09.

(5) City, State MARSHALL, MO	(6) Airport MARSHALL MEML MUNI	(7) Effective Date DEC 22 2005	(8) Amdt. No. ORIG
--	--	--	------------------------------