

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
CTB VORTAC	SBX NDB	077.11 / 19.22	6000	SBX NDB	
BRADZ INT	SBX NDB	358.46 / 23.57	6000	CLIMBING RIGHT TURN TO 5500 IN SBX NDB HOLDING PATTERN.	
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 212.50 INBOUND. CHART FAS OBST: 3809 AAO 484120N/1114433W FAC CROSSES RWY C/L EXTENDED 3002 FROM THLD.	

1. PT L SIDE OF COURSE 032.50 OUTBOUND 5500 FT WITHIN 10 MILES OF SBX NDB (IAF)
 2. _____
 3. FAC 212.50 FAF _____ DIST FAF TO MAP _____ THLD _____
 4. MIN. ALT _____
 8. MSA FROM: SBX NDB 080-170 5700, 170-260 6200, 260-350 5700, 350-080 8200

MAG VAR: 15E EPOCH YEAR: 2005

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		X						
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-23	4240	1	797	4240	1 1/4	797	4240	2 1/4	797		NA				
CIRCLING	4240	1	797	4240	1 1/4	797	4240	2 1/4	797		NA				

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: USE CUT BANK ALTIMETER SETTING; IF NOT RECEIVED, USE GREAT FALLS ALTIMETER SETTING AND INCREASE ALL MDA'S 120 FEET.

CITY AND STATE SHELBY, MT	ELEVATION: 3443 TDZE: 3443	FACILITY IDENTIFIER: SBX	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 23, AMDT 7 MAR 15 2007	SUP NDB OR GPS RWY
	AIRPORT NAME: SHELBY			23
				AMDT 6
				DATE 02/04/1993