

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW28 CLIMBING RIGHT TURN TO 2000 DIRECT ZOKAD AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 549 AAO 312503N/0832437W YEPUB TO RW28: 3.04/40.	
IFM VOR	ZOKAD (FO)	096.52 / 11.56	2000		
OTK VOR/DME (IAF)	ZOKAD (NOPT) (FB)	004.21 / 38.09	2000		
ZOKAD (IF/IAF)	YEPUB (FB)	277.55 / 6.10	2000		
YEPUB (FAF)	RW28 (MAP) (FO)	277.49 / 5.02			
RW28 (MAP)	755 MSL	277.49			
755 MSL	ZOKAD (FO)		2000		
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD E ZOKAD, RT, 277.55 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>277.49</u> FAF: YEPUB <u> </u> DIST FAF TO MAP: <u>5.02</u> THLD: <u>5.02</u> 4. MIN. ALT: ZOKAD 2000, YEPUB 2000 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW28 2500				MAG VAR: 3W EPOCH YEAR: 1990	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A		STANDARD @
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	800	1	450	800	1
CIRCLING	900	1	545	920	1
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. @ CAT D 800-2 1/4 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MOULTRIE ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND LNAV CATS C AND D AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE. (SEE FORM 8260-10)					
CITY AND STATE TIFTON, GA		ELEVATION: 355 TDZE: 350 AIRPORT NAME: HENRY TIFT MYERS		FACILITY IDENTIFIER: RNAV PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 28, ORIG-A 10 JANUARY 2013	
				SUP: AMDT: ORIG DATED 09/23/2010	

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: RWY 28 STRAIGHT-IN AND CIRCLING AND CIRCLING TO RWY 10/15 NA AT NIGHT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT IFM VOR ON V578 WESTBOUND.

CITY AND STATE

TIFTON, GA

ELEVATION: 355

TDZE: 350

AIRPORT NAME:

HENRY TIFT MYERS

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 28, ORIG-A

10 JANUARY 2013

SUP:

AMDT: ORIG

DATED: 09/23/2010

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible][illegible]

CITY AND STATE TIFTON, GA	ELEVATION: 355	TDZE: 350	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 28, ORIG-A	AMDT: ORIG
	HENRY TIFT MYERS		RNAV	10 JANUARY 2013	DATED: 09/23/2010

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	IFM	IFM	010		IF		FB					
	IFM	ZOKAD	020		TF		FO	2.0	096.5 (093.5T)	011.6	AA 02000	
	IFM	ZOKAD	030	IAF	HF	R	FO		277.6 (274.6T)	004.0	AA 02000	
	OTK	OTK	010	IAF	IF		FB					
	OTK	ZOKAD	020		TF		FB	1.0	004.2 (001.2T)	038.1	AA 02000	
		ZOKAD	010	FACF	IF		FB				AA 02000	
		YEPUB	020	FAF	TF		FB	0.5	277.6 (274.6T)	006.1	AA 02000	
		RW28	030	MAP	TF		FO	0.3	277.5 (274.5T)	005.0	AT 00379	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		277.5 (274.5T)		AA 00755	
	ZOKAD	050		DF	R	FO				AA 02000	
	ZOKAD	060		HM	R	FO		277.6 (274.6T)	004.0	AA 02000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	IFM	N312543.17	W0832919.99	N3125.720	W08329.333
	OTK	N304649.60	W0831647.02	N3046.827	W08316.784
	YEPUB	N312528.72	W0832257.13	N3125.479	W08322.952
	ZOKAD	N312459.81	W0831550.79	N3124.997	W08315.847
	RW28	N312552.23	W0832848.15	N3125.871	W08328.803

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW28	00339	40

CITY AND STATE TIFTON, GA	ELEVATION: 355	TDZE: 350	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: HENRY TIFT MYERS		RNAV	RNAV (GPS) RWY 28, ORIG-A	AMDT: ORIG
				10 JANUARY 2013	DATED: 09/23/2010