

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW16 CLIMB TO 4000 DIRECT ZIPUD AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000. ADDITIONAL FLIGHT DATA: HOLD S, RT, 344.49 INBOUND. CHART FAS OBST: 1269 TREE 454327N/0965949W DISTANCE TO THLD FROM 316 HAT: 0.86 NM. WAAS CHANNEL # 50538 REFERENCE PATH ID: W16A CHART CIRCLING ICON. CHART WHEATON AWOS-3. LTP HAE: 327.6 M							
BUNKI (IF/IAF)		WITVU (FB)		164.41 / 5.00				2800									
WITVU (FAF)		RW16 (MAP) (FO)		164.43 / 5.03													
RW16 (MAP)		1478 MSL		164.43				4000									
1478 MSL		ZIPUD (FO)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N BUNKI, RT, 164.41 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: 164.43 FAF: WITVU DIST FAF TO MAP: 5.03 THLD: 5.03 4. MIN. ALT: BUNKI 4000, WITVU 2800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2800 GS ALT AT: WITVU 2800 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR 8. MSA FROM: _____														MAG VAR: 3E		EPOCH YEAR: 2020	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		<input checked="" type="checkbox"/>					
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	1478	1 1/8	316	1478	1 1/8	316		NA			NA						
LNAV/VNAV DA	1498	1 1/8	336	1498	1 1/8	336		NA			NA						
LNAV MDA	1600	1	438	1600	1	438		NA			NA						
CIRCLING	1660	1	498	1700	1	538		NA			NA						
NOTES: CHART NOTE: CIRCLING NA TO RWYS 4 AND 22. CHART NOTE: BARO-VNAV NA. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. (CONTINUED ON PAGE 2)																	
CITY AND STATE		ELEVATION: 1162 TDZE: 1162				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
SISSETON, SD		AIRPORT NAME: SISSETON MUNI						RNAV (GPS) RWY 16, ORIG 21 JULY 2016				AMDT: NONE					
														DATED			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: USE WHEATON ALTIMETER SETTING; WHEN NOT RECEIVED, USE ORTONVILLE ALTIMETER SETTING AND INCREASE LPV DA TO 1496 FEET, LNAV/VNAV DA TO 1516 FEET AND ALL MDA 20 FEET. INCREASE LNAV/VNAV CATS A/B VISIBILITY 1/8 MILE.

TAA

	FROM	TO	ALT
1.	074/30 CW 254/30 (NOPT)	BUNKI (IF/IAF) (FB)	4000
2.	254/30 CW 074/30	BUNKI (IF/IAF) (FO)	4000

QUALITY
10
CHECKED

CITY AND STATE
SISSETON, SD

ELEVATION: 1162 **TDZE: 1162**
AIRPORT NAME:
SISSETON MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, ORIG
21 JULY 2016

SUP:
AMDT: **NONE**
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	8D3
RUNWAY	RW16
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W16A
LTP/FTP LATITUDE	454024.3430N
LTP/FTP LONGITUDE	0965942.9730W
LTP/FTP ELLIPSOIDAL HEIGHT	+03276
FPAP LATITUDE	453857.3910N
FPAP LONGITUDE	0965915.3745W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1712
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

8B25FDFB

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+03534
FPAP ORTHOMETRIC HEIGHT	+03534

QUALITY
10
CHECKED

CITY AND STATE

SISSETON, SD

ELEVATION: 1162

TDZE: 1162

AIRPORT NAME:

SISSETON MUNI

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 16, ORIG

21 JULY 2016

SUP:

AMDT:

DATED:

NONE

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33											Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.																																																																																																																																																
<div style="margin-bottom: 10px;">ARINC SUMMARY - 8D3</div> <div style="margin-bottom: 10px;">ROUTES</div> <table style="width:100%; border-collapse: collapse; font-family: monospace; font-size: small;"> <thead> <tr> <th style="text-align: left;">TRANSITION</th> <th style="text-align: left;">WPT SEQ</th> <th style="text-align: left;">WPT NAME</th> <th style="text-align: left;">LEG TYPE</th> <th style="text-align: left;">FB/FO</th> <th style="text-align: left;">RNP</th> <th style="text-align: left;">MAG CRS</th> <th style="text-align: left;">REC NAV</th> <th style="text-align: left;">ANGLE</th> <th style="text-align: left;">TURN DIR</th> <th style="text-align: left;">CENTER FIX</th> <th style="text-align: left;">TURN RADIUS</th> <th style="text-align: left;">ALTITUDE DESCRIPTION & VALUE</th> <th style="text-align: left;">SPEED LIMIT DESCRIPTION & VALUE</th> <th style="text-align: left;">WPT DESCRIPTION CODE</th> </tr> </thead> <tbody> <tr> <td>BUNKI</td> <td>010</td> <td>BUNKI</td> <td>HF</td> <td>FO</td> <td></td> <td>164.4</td> <td></td> <td></td> <td>R</td> <td></td> <td></td> <td>AA 04000</td> <td></td> <td>EE A</td> </tr> <tr> <td></td> <td>010</td> <td>BUNKI</td> <td>IF</td> <td>FB</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 04000</td> <td></td> <td>E I</td> </tr> <tr> <td></td> <td>020</td> <td>WITVU</td> <td>TF</td> <td>FB</td> <td>1.0</td> <td>164.4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 02800</td> <td></td> <td>E F</td> </tr> <tr> <td></td> <td>030</td> <td>RW16</td> <td>TF</td> <td>FO</td> <td>0.3</td> <td>164.4</td> <td></td> <td>3.00</td> <td></td> <td></td> <td></td> <td>AT 01199</td> <td></td> <td>GY M</td> </tr> <tr> <td></td> <td>040</td> <td></td> <td>CA</td> <td>FB</td> <td></td> <td>164.4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 01478</td> <td></td> <td>M</td> </tr> <tr> <td></td> <td>050</td> <td>ZIPUD</td> <td>DF</td> <td>FO</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 04000</td> <td></td> <td>EY</td> </tr> <tr> <td></td> <td>060</td> <td>ZIPUD</td> <td>HM</td> <td>FO</td> <td></td> <td>344.5</td> <td></td> <td></td> <td>R</td> <td></td> <td></td> <td>AA 04000</td> <td></td> <td>EE</td> </tr> </tbody> </table> <div style="margin-bottom: 10px;">POINTS</div> <table style="width:100%; border-collapse: collapse; font-family: monospace; font-size: small;"> <thead> <tr> <th style="text-align: left;">POINT NAME</th> <th style="text-align: left;">LATITUDE</th> <th style="text-align: left;">LONGITUDE</th> </tr> </thead> <tbody> <tr> <td>BUNKI</td> <td>N455011.35</td> <td>W0970249.93</td> </tr> <tr> <td>WITVU</td> <td>N454518.62</td> <td>W0970116.56</td> </tr> <tr> <td>ZIPUD</td> <td>N453004.83</td> <td>W0965626.84</td> </tr> </tbody> </table> <div style="margin-bottom: 10px;">RUNWAYS</div> <table style="width:100%; border-collapse: collapse; font-family: monospace; font-size: small;"> <thead> <tr> <th style="text-align: left;">RUNWAY</th> <th style="text-align: left;">THRESHOLD LATITUDE</th> <th style="text-align: left;">THRESHOLD LONGITUDE</th> <th style="text-align: left;">THRESHOLD ELEVATION</th> <th style="text-align: left;">PROCEDURE TCH</th> </tr> </thead> <tbody> <tr> <td>RW16</td> <td>N454024.34</td> <td>W0965942.97</td> <td>01159</td> <td>40</td> </tr> </tbody> </table>														TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE	BUNKI	010	BUNKI	HF	FO		164.4			R			AA 04000		EE A		010	BUNKI	IF	FB								AA 04000		E I		020	WITVU	TF	FB	1.0	164.4						AA 02800		E F		030	RW16	TF	FO	0.3	164.4		3.00				AT 01199		GY M		040		CA	FB		164.4						AA 01478		M		050	ZIPUD	DF	FO								AA 04000		EY		060	ZIPUD	HM	FO		344.5			R			AA 04000		EE	POINT NAME	LATITUDE	LONGITUDE	BUNKI	N455011.35	W0970249.93	WITVU	N454518.62	W0970116.56	ZIPUD	N453004.83	W0965626.84	RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH	RW16	N454024.34	W0965942.97	01159	40
TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE																																																																																																																																													
BUNKI	010	BUNKI	HF	FO		164.4			R			AA 04000		EE A																																																																																																																																													
	010	BUNKI	IF	FB								AA 04000		E I																																																																																																																																													
	020	WITVU	TF	FB	1.0	164.4						AA 02800		E F																																																																																																																																													
	030	RW16	TF	FO	0.3	164.4		3.00				AT 01199		GY M																																																																																																																																													
	040		CA	FB		164.4						AA 01478		M																																																																																																																																													
	050	ZIPUD	DF	FO								AA 04000		EY																																																																																																																																													
	060	ZIPUD	HM	FO		344.5			R			AA 04000		EE																																																																																																																																													
POINT NAME	LATITUDE	LONGITUDE																																																																																																																																																									
BUNKI	N455011.35	W0970249.93																																																																																																																																																									
WITVU	N454518.62	W0970116.56																																																																																																																																																									
ZIPUD	N453004.83	W0965626.84																																																																																																																																																									
RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH																																																																																																																																																							
RW16	N454024.34	W0965942.97	01159	40																																																																																																																																																							
CITY AND STATE SISSETON, SD		ELEVATION: 1162 TDZE: 1162 AIRPORT NAME: SISSETON MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 16, ORIG 21 JULY 2016			<div style="text-align: right; color: green; font-weight: bold; font-size: x-small;"> QUALITY 10 CHECKED </div> SUP: AMDT: NONE DATED:																																																																																																																																																		