

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
LIBRT	ONE	LIBRT1.LIBRT	NONE		15 Nov 2012

TYPE: RNAV SID

DP ROUTE DESCRIPTION:

TAKEOFF RWY 04: CLIMB HEADING 035.80 TO 1440, THEN LEFT TURN DIRECT AGLOW, THEN ON DEPICTED ROUTE TO LIBRT, THEN ON HEADING 073.23, EXPECT VECTORS ON COURSE. MAINTAIN 4000 OR AS ASSIGNED BY ATC. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: RADAR REQUIRED.

NOTE: DME/DME/IRU OR GPS REQUIRED

NOTE: RNAV 1

TAKEOFF MINIMUMS: RWY 17, 35, 22, NA-ATC. RWY 04, STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 4000.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 4, TREES BEGINNING 2029 FT FROM DEPARTURE END OF RUNWAY, 62 FT RIGHT OF CENTERLINE UP TO 81 FT AGL/999 FT MSL. TREES BEGINNING 1422 FT FROM DEPARTURE END OF RUNWAY, 3 FT LEFT OF CENTERLINE UP TO 76 FT AGL/995 FT MSL. POLES BEGINNING 427 FT FROM DEPARTURE END OF RUNWAY, 483 FT RIGHT OF CENTERLINE UP TO 44 FT AGL/1044 FT MSL. OBSTRUCTION LIGHTS ON FENCE BEGINNING 2 FT FROM DEPARTURE END OF RUNWAY, 500 FT RIGHT OF CENTERLINE UP TO 30 FT AGL/ 948 FT MSL. ANTENNA ON BUILDING 395 FT FROM DEPARTURE END OF RUNWAY, 277 FT RIGHT OF CENTERLINE 15 FT AGL/954 FT MSL. LIGHT 606 FT FROM DEPARTURE END OF RUNWAY, 599 FT RIGHT OF CENTERLINE, 18 FT AGL/982 FT MSL. BUILDING 400 FT FROM DEPARTURE END OF RUNWAY, 345 FT RIGHT OF CENTERLINE, 12 FT AGL/951 FT MSL.

CONTROLLING OBSTACLES:

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KLYH 8 W EPOCH YR: 1995

DME/DME ASSESSMENT: SAT (RNP 1.0)

QUALITY
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
LIBRT	ONE	LIBRT1.LIBRT	NONE		15 Nov 2012

AIRPORTS SERVED:

LYNCHBURG RGNL/PRESTON GLENN FLD

LYNCHBURG, VA

COMMUNICATIONS:

ATIS, LYH GND CON, LYH ATCT, ROA DEP CON

FIXES AND/OR NAVAIDS:

CHART: LYH VORTAC.