

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.48 MILES AFTER LUK NDB							
FLM VOR/DME MOAKS INT (IF/IAF)		LUK NDB		001.32 / 30.62				2900		CLIMBING LEFT TURN TO 2500 ON HEADING 185 AND CVG R-109 TO CALIF INT AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2600.							
		LUK NDB (NOPT)		223.79 / 10.58				1900									
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 288.87 INBOUND. FAS OBST: 1109 AAO 390943N/0842200W LUK NDB TO RW25: 2.88/55.							
1. PT <u>L</u> SIDE OF COURSE <u>051.49</u> OUTBOUND <u>2600</u> FT WITHIN <u>10</u> MILES OF <u>LUK NDB</u> (IAF)																	
2.																	
3. FAC <u>231.49</u> FAF <u>LUK NDB</u> DIST FAF TO MAP <u>4.48</u> THLD <u>4.48</u>																	
4. MIN. ALT <u>LUK NDB 1900</u>																	
8. MSA FROM: <u>LUK NDB 3000</u>																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: <u>N A</u>		@							
CATEGORY =====>	A			B			C			D			E				
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-25	1420	1 1/4	945	1420	1 1/4	945	1420	2 1/2	945	1420	2 1/2	945	1420	3	937		
CIRCLING	1420	1 1/4	937	1420	1 1/4	937	1420	2 3/4	937	1420	3	937					
NOTES: CHART NOTE: CIRCLING TO RWY 3L AND 7 NA AT NIGHT. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CINCINNATI/NORTHERN KENTUCKY INTL (SEE FORM 8260-10)																	
CITY AND STATE CINCINNATI, OH				ELEVATION: 483      THRE: 475 AIRPORT NAME: CINCINNATI MUNI AIRPORT LUNKEN FIELD		FACILITY IDENTIFIER: LUK		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: NDB RWY 25, AMDT 12 20 SEPTEMBER 2012				SUP		QUALITY 2 CHECKED			
												AMD'T				11	
												DATE				10/20/2011	

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):****ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET; INCREASE S-25 CAT B AND CIRCLING CAT B/C****VISIBILITY 1/4 MILE, S-25 CATS C/D VISIBILITY 1/2 MILE.****CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MOAKS ON V5 NORTHEAST BOUND.****CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 25 PROCEDURE NA AT NIGHT.**

QUALITY  
2  
CHECKED

CITY AND STATE

CINCINNATI, OH

ELEVATION: 483

THRE: 475

AIRPORT NAME:

CINCINNATI MUNI AIRPORT LUNKEN FIELD

FACILITY  
IDENTIFIER:

LUK

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 25, AMDT 12

20 SEPTEMBER 2012

SUP:

AMDT: 11

DATED: 10/20/2011