

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>VOR STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>					
<b>FROM</b>		<b>TO</b>		<b>COURSE AND DISTANCE</b>				<b>ALTITUDE</b>		<b>MAP: ZIDVA/ENA 9.40 DME</b>					
SWANS/ENA 10.00 DME CCW (IAF)		FANKA/ENA 10.00 DME (NOPT)		10.00 DME ARC				1900		CLIMBING RIGHT TURN TO 3700 ON HEADING 184 AND ON ENA R-138 TO CABUG/ENA 12.00 DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3700.					
FANKA/ENA 10.00 DME (IF)		ENA VOR/DME		131.97 / 10.00				1900							
										<b>ADDITIONAL FLIGHT DATA:</b> HOLD SE, RT, 318.00 INBOUND. CHART FAS OBST: 399 TREE 602942N/1510015W OBST: 437 AAO 603148N/1510254W CHART ENA R-028 AT SWANS. FAC CROSSES MID POINT OF RWY 07-25. CHART MAXIMUM 6000 AT ENA VOR/DME					
1. PT <u>R</u> SIDE OF COURSE <u>311.97</u> OUTBOUND <u>1900</u> FT WITHIN <u>10</u> MILES OF <u>ENA VOR/DME</u> (IAF)														MAG VAR: 19E      EPOCH YEAR: 2010	
2. _____															
3. FAC <u>131.97</u> FAF <u>ENA VOR/DME</u> DIST FAF TO MAP _____ THLD _____															
4. MIN. ALT <u>ENA VOR/DME 1900, CANIL/ENA 7.00 DME 1020*</u>															
8. MSA FROM: <u>ENA VOR/DME 030-190 3500, 190-030 2200</u>															
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY =====>		A		B		C		D		E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	840	1	727	840	1	727	840	2	727	860	2 1/2	747			
<b>NOTES:</b> CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE KENAI ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET AND CAT C VISIBILITY 1/4 MILE. *1060 WHEN USING KENAI ALTIMETER SETTING.															
CITY AND STATE SOLDOTNA, AK		ELEVATION: 113 AIRPORT NAME:  SOLDOTNA		TDZE:		FACILITY IDENTIFIER: ENA		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME-A, AMDT 7B 20 SEPTEMBER 2012				SUP		VOR-A	
												AMDT		7A	
												DATE		05/31/2012	

QUALITY  
 1  
 CHECKED