

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: SITYO CLIMB TO 7000 THEN CLIMBING LEFT TURN TO 11600 DIRECT RADIO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 166.03 INBOUND. FAS OBST: 6060 AAO 372012N/1042117W 6125 AAO 372118N/1041924W. CHART CIRCLING ICON FAC CROSSES 240 FT WEST OF RWY 03-21 AND RWY 09-27 INTERSECTION.	
JOGL (IF/IAF)	WOTIX (FB)	166.48 / 7.05	7800		
WOTIX (FAF)	SITYO (MAP) (FO)	166.49 / 5.09			
SITYO (MAP)	7000 MSL	166.49	7000		
7000 MSL	RADIO (FO)		11600		
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N JOGL, RT, 166.48 INBOUND, 8900 FT. IN LIEU OF PT (IAF) 3. FAC: <u>166.49</u> FAF: <u>WOTIX</u> DIST FAF TO MAP: <u>5.09</u> THLD: <u> </u> 4. MIN. ALT: JOGL 8900, WOTIX 7800 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u> </u> 8. MSA FROM: SITYO 13900				MAG VAR: 10E EPOCH YEAR: 1995	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A		STANDARD @
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
CIRCLING	6320	1	558	6320	1
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PUEBLO MEMORIAL ALTIMETER SETTING AND INCREASE ALL MDA 300 FEET AND VISIBILITY CATS A AND B 1/4 MILE, VISIBILITY CAT C 1 1/4, AND VISIBILITY CAT D 1/2 MILE. (SEE FORM 8260-10)					
CITY AND STATE TRINIDAD, CO		ELEVATION: 5762 TDZE: AIRPORT NAME: PERRY STOKES		FACILITY IDENTIFIER: RNAV PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-B, AMDT 1 12 DECEMBER 2013	
		SUP: AMDT: ORIG-A DATED 07/10/2003			

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: JOGEL ARRIVALS DESCEND TO 8900 IN JOGEL HOLDING PATTERN PRIOR TO COMMENCING APPROACH.

QUALITY
2
CHECKED

CITY AND STATE
TRINIDAD, CO

ELEVATION: 5762 TDZE:
AIRPORT NAME:
PERRY STOKES

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-B, AMDT 1
12 DECEMBER 2013

SUP:
AMDT: ORIG-A
DATED: 07/10/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KTADK2FRNV-B	AJOJEL	010JOJELK2EA0EE	AR	HF			16650070	+	08900	18000		B	JC
SUSAP KTADK2FRNV-B	R	010JOJELK2EA0E	I	IF				+	08900	18000		B	JC
SUSAP KTADK2FRNV-B	R	020WOTIXK2EA0E	F	051TF			16650071	+	07800		SITYO K2EAB	JC	
SUSAP KTADK2FRNV-B	R	030SITYOK2EA0EY	M	031TF			16650051		06560	000		B	JC
SUSAP KTADK2FRNV-B	R	040	0	M	CA		1665	+	07000			B	JC
SUSAP KTADK2FRNV-B	R	050RADIOK2EA0EY	L	DF				+	11600			B	JC
SUSAP KTADK2FRNV-B	R	060RADIOK2EA0EE	R	HM			16600070	+	11600			B	JC

[illegible]

QUALITY
2
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	JOGEL	JOGEL	010	IAF	HF	R	FO		166.5 (176.5T)	007.0	AA 08900	
		JOGEL	010	FACF	IF		FB				AA 08900	
		WOTIX	020	FAF	TF		FB	0.5	166.5 (176.5T)	007.1	AA 07800	
		SITYO	030	MAP	TF		FO	0.3	166.5 (176.5T)	005.1	AT 06560	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		166.5 (176.5T)		AA 07000	
	RADIO	050		DF	L	FO				AA 11600	
	RADIO	060		HM	R	FO		166.0 (176.0T)	007.0	AA 11600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	JOGEL	N372759.10	W1042124.54	N3727.985	W10421.409
	RADIO	N374122.24	W1042234.40	N3741.371	W10422.573
	SITYO	N371551.21	W1042028.51	N3715.854	W10420.475
	WOTIX	N372056.65	W1042051.95	N3720.944	W10420.866

QUALITY
2
CHECKED

CITY AND STATE TRINIDAD, CO	ELEVATION: 5762	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-B, AMDT 1 12 DECEMBER 2013	SUP:
	AIRPORT NAME: PERRY STOKES				AMDT: ORIG-A
					DATED: 07/10/2003