

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: GRO NDB					
ERTTS INT/UNZ 46.00 DME		GRO NDB		087.09 / 12.29				3100		CLIMBING RIGHT TURN TO 2000 ON HEADING 360 THEN CONTINUE CLIMBING RIGHT TURN TO 3100 DIRECT GRO NDB AND HOLD.					
KAQTU/UNZ 23.00 DME		GRO NDB		030.74 / 29.09				3100							
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 260.00 INBOUND. CHART FAS OBST: 661 TREE 141022N/1451457E CHART 3100 PRIOR TO GRO NDB IN PROFILE. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 1788 FROM THLD.					
1. PT <u>  L  </u> SIDE OF COURSE <u>  080.00  </u> OUTBOUND <u>  2000  </u> FT WITHIN <u>  10  </u> MILES OF <u>  GRO NDB  </u> (IAF)															
2. _____															
3. FAC <u>  260.00  </u> FAF _____ DIST FAF TO MAP _____ THLD _____															
4. MIN. ALT _____															
8. MSA FROM: GRO NDB 2900										MAG VAR: 2E				EPOCH YEAR: 1985	
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: NA		@							
CATEGORY =====>		A		B		C		D		E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-27	1120	1	513	1120	1	513	1120	1 3/8	513	1120	1 3/8	513			
CIRCLING	1120	1	513	1120	1	513	1120	1 1/2	513	1160	2	553			
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ANDERSEN AFB ALTIMETER SETTING AND INCREASE ALL MDA 320 FT, INCREASE S-27 CAT B VISIBILITY 1/4 MILE, CAT C,D VISIBILITY 1 1/8 MILE, CIRCLING CAT A,B VISIBILITY 1/4 MILE, CAT C 1 MILE, CAT D 3/4 MILE. CHART NOTE: CIRCLING NA S OF RWY 09-27. (SEE FORM 8260-10)															
CITY AND STATE				ELEVATION: 607		THRE: 607		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP	
ROTA ISLAND, CQ				AIRPORT NAME:		BENJAMIN TAISACAN MANGIONA INTL		GRO		NDB RWY 27, AMDT 4 6 FEBRUARY 2014				AMDT 3D	
													DATE 02/09/2012		

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES, (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: STRAIGHT-IN AND CIRCLING TO RWY 27 NA AT NIGHT.

CITY AND STATE

ROTA ISLAND, CQ

ELEVATION: 607

THRE: 607

AIRPORT NAME:

BENJAMIN TAISACAN MANGIONA INTL

FACILITY  
IDENTIFIER:

GRO

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

NDB RWY 27, AMDT 4

6 FEBRUARY 2014

SUP:

AMDT: 3D

DATED: 02/09/2012