

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CHAMBERLAIN, SD	CHAMBERLAIN MUNI	13 DECEMBER 2012	1

TAKEOFF MINIMUMS:

RWY 18, 36, NA-ENVIRONMENTAL
RWY 13, 31 STANDARD

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 13, TREES LEFT AND RIGHT OF CENTERLINE BEGINNING 100 FT FROM DER, UP TO 47 FT AGL/1725 FT MSL.
POLE 1116 FT FROM DER, 712 FT LEFT OF CENTERLINE, 32 FT AGL/1710 FT MSL.

NOTE: RWY 31, RISING TERRAIN 91 FT FROM DER, 290 FT RIGHT OF CENTERLINE, 1702 FT MSL.
VEHICLE ON ROAD 1072 FT FROM DER, FROM 553 TO 781 FT RIGHT OF CENTERLINE, 15 FT AGL/1728 FT MSL.
TREES LEFT AND RIGHT OF CENTERLINE BEGINNING 1359 FT FROM DER, UP TO 71 FT AGL/1767 FT MSL.
POLE 1201 FT FROM DER, 701 FT RIGHT OF CENTERLINE, 45 FT AGL/1741 FT MSL.

CONTROLLING OBSTACLES:

