

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
MASON, TX	MASON COUNTY	15 NOVEMBER 2012	1

TAKEOFF MINIMUMS:

RWY 13, 18, 31 STANDARD.
RWY 36, 300-1 OR STANDARD WITH MINIMUM CLIMB OF 299 FT PER NM TO 1800.

TEXTUAL DEPARTURE PROCEDURES:

RWY 18: CLIMB HEADING 181.04 TO 2100 FT BEFORE TURNING RIGHT.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 13, TERRAIN BEGINNING 305 FT FROM DER, 99 FT RIGHT OF CENTERLINE, UP TO 1500 FT MSL. TERRAIN BEGINNING 36 FT FROM DER, 106 FT LEFT OF CENTERLINE, UP TO 1520 FT MSL.
NOTE: RWY 18, TERRAIN BEGINNING 163 FT FROM DER, 185 FT RIGHT OF CENTERLINE, UP TO 1520 FT MSL.
NOTE: RWY 36, TERRAIN BEGINNING 361 FT FROM DER, 6 FT LEFT OF CENTERLINE, UP TO 1533 FT MSL. TL TOWER 3061 FT FROM DER, 1185 FT LEFT OF CENTERLINE, 95 FT AGL/ 1628 FT MSL. MULTIPLE TL TOWERS BEGINNING 3940 FT FROM DER, 194 FT LEFT OF CENTERLINE, 85 FT AGL/ 1636 FT MSL. MULTIPLE TL TOWERS BEGINNING 4427 FT FROM DER, 304 FT RIGHT OF CENTERLINE, 90 FT AGL/ 1667 FT MSL.

CONTROLLING OBSTACLES:

RWY 18: 2195 FT MSL TOWER 304203.60N/0991400.20W
RWY 36: 1667 FT MSL TL TOWER 304458.09N/0991058.68W

