



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HELER (IF)	JIKTA (FB)	260.44 / 6.15	6600
JIKTA (FAF)	RW26L (MAP) (FB)	260.44 / 5.93	
RW26L (MAP)	4849 MSL	260.44	
4849 MSL	MERTZ (FO)		7000

NOTES, (CONT.):

ALL DA 183 FEET AND ALL MDA 200 FEET; INCREASE LPV ALL CATS VISIBILITY 1/2 MILE, LNAV/VNAV ALL CATS AND LNAV CATS C/D VISIBILITY 5/8 MILE, CIRCLING CATS A/B VISIBILITY 1/4 MILE AND CIRCLING CATS C/D VISIBILITY 3/4 MILE.  
 CHART NOTE: BARO-VNAV AND VDP NA WITH LA JUNTA ALTIMETER SETTING.  
 CHART PLANVIEW NOTE AT HELER : MAX 210 KIAS.

CITY AND STATE

PUEBLO, CO

ELEVATION: 4729

THRE: 4649

AIRPORT NAME:

PUEBLO MEMORIAL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO / AMDT NO / EFFECTIVE DATE:

RNAV (GPS) RWY 26L, ORIG

27 JUNE 2013

SUP:

AMDT: NONE

DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0  
SBAS SERVICE PROVIDER IDENTIFIER 0  
AIRPORT IDENTIFIER KPUB  
RUNWAY RW26L  
APPROACH PERFORMANCE DESIGNATOR 0  
ROUTE INDICATOR 0  
REFERENCE PATH DATA SELECTOR W26A  
REFERENCE PATH IDENTIFIER (APPROACH ID) 381716.7525N  
LTP/FTP LATITUDE 1042824.6630W  
LTP/FTP LONGITUDE +13973  
LTP/FTP ELLIPSOIDAL HEIGHT 381713.6300N  
FPAP LATITUDE 1043036.2400W  
FPAP LONGITUDE 00061.6  
THRESHOLD CROSSING HEIGHT (TCH) F  
TCH UNITS SELECTOR (METERS OR FEET USED) 03.00  
GLIDEPATH ANGLE (GPA) 106.75  
COURSE WIDTH AT THRESHOLD 0000  
LENGTH OFFSET 40.0  
HORIZONTAL ALERT LIMIT (HAL) 35.0  
VERTICAL ALERT LIMIT (VAL)

CRC REMAINDER

9B5612B0

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K2  
LTP ORTHOMETRIC HEIGHT +14169  
FPAP ORTHOMETRIC HEIGHT +14169

CITY AND STATE

PUEBLO, CO

ELEVATION: 4729

THRE: 4649

AIRPORT NAME:

PUEBLO MEMORIAL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 26L, ORIG

27 JUNE 2013

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KPUBK2FR26L	ADRAKE	010DRAKEK2EA0E	IF						18000		A JS	
SUSAP	KPUBK2FR26L	ADRAKE	020BONUHK2EA0E	A 020TF		13650157		+ 07700				A JS	
SUSAP	KPUBK2FR26L	ADRAKE	030HELERK2EA0EE	B 010TF		17050060		+ 07000				A JS	
SUSAP	KPUBK2FR26L	AORWAY	010ORWAYK2EA0E	A IF						18000		A JS	
SUSAP	KPUBK2FR26L	AORWAY	020HELERK2EA0EE	B 010TF		27010077		+ 07000				A JS	
SUSAP	KPUBK2FR26L	APUB	010PUB K2D 0V	IF						18000		A JS	
SUSAP	KPUBK2FR26L	APUB	020HELERK2EA0EY	020TF		08210100		+ 07200				A JS	
SUSAP	KPUBK2FR26L	APUB	030HELERK2EA0EE	AR HF		26040060		+ 07000				A JS	
SUSAP	KPUBK2FR26L	ASTAXX	010STAXXK2EA0E	IF						18000		A JS	
SUSAP	KPUBK2FR26L	ASTAXX	020REDHIK2EA0E	A 020TF		34580129		+ 07000				A JS	
SUSAP	KPUBK2FR26L	ASTAXX	030HELERK2EA0EE	B 010TF		34580060		+ 07000				A JS	
SUSAP	KPUBK2FR26L	AVIGIL	010VIGILK2EA0E	IF						18000		A JS	
SUSAP	KPUBK2FR26L	AVIGIL	020REDHIK2EA0E	A 020TF		03570216		+ 07900				A JS	
SUSAP	KPUBK2FR26L	AVIGIL	030HELERK2EA0EE	B 010TF		34580060		+ 07000				A JS	
SUSAP	KPUBK2FR26L	R	010HELERK2EA0E	I IF				+ 07000		18000		A JS	
SUSAP	KPUBK2FR26L	R	020JIKTAK2EA1E	F 051TF		26040062		+ 06600			RW26L K2PGA	JS	
SUSAP	KPUBK2FR26L	R	020JIKTAK2EA2WALPV		ALNAV/VNAV	ALNAV						JS	
SUSAP	KPUBK2FR26L	R	030RW26LK2PGOG	M 031TF		26040059		04710		-300		A JS	

CITY AND STATE  PUEBLO, CO	ELEVATION: 4729	THRE: 4649	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 26L, ORIG	AMDT: NONE
	PUEBLO MEMORIAL		RNAV	27 JUNE 2013	DATED:

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KPUBK2FR26L R	040	0 M	CA	2604	+ 04849	A JS
SUSAP KPUBK2FR26L R	050MERTZK2EA0EY		DF		+ 07000	A JS
SUSAP KPUBK2FR26L R	060MERTZK2EA0EE L	HM		29000070	+ 07000	A JS

	1	2	3	4	5	6	7	8	9	0	1	2	3
RUNWAY	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												
-----													
SUSAP KPUBK2GRW26L	0104982603	N38171675W104282466+0200	+1397304649000062150I										

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												
-----													
SUSAP KPUBK2PR26L	RW26L001	0000W26A0N3817167525W10428246630+139730300N3817136300W10430362400106750000000616F4003509B5612B0											
SUSAP KPUBK2PR26L	RW26L002E	+14169+14169LPV	53531										

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												
-----													
SUSAP KPUBK2SRW26LK2PG	0	18018009325	M										

CITY AND STATE <b>PUEBLO, CO</b>	ELEVATION: <b>4729</b>	THRE: <b>4649</b>	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: <b>PUEBLO MEMORIAL</b>		<b>RNAV</b>	<b>RNAV (GPS) RWY 26L, ORIG</b>	AMDT: <b>NONE</b>
				<b>27 JUNE 2013</b>	DATED:

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
 FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
DRAKE	DRAKE	DRAKE	010		IF		FB					
DRAKE	DRAKE	BONUH	020	IAF	TF		FB	2.0	136.5(144.5T)	015.7	AA 07700	
DRAKE	DRAKE	HELER	030		TF		FB	1.0	170.5(178.5T)	006.0	AA 07000	
ORWAY	ORWAY	ORWAY	010	IAF	IF		FB					
ORWAY	ORWAY	HELER	020		TF		FB	1.0	270.1(278.1T)	007.7	AA 07000	
PUB	PUB	PUB	010		IF		FB					
PUB	PUB	HELER	020		TF		FO	2.0	082.1(090.1T)	010.0	AA 07200	
PUB	PUB	HELER	030	IAF	HF	R	FO		260.4(268.4T)	006.0	AA 07000	
STAXX	STAXX	STAXX	010		IF		FB					
STAXX	STAXX	REDHI	020	IAF	TF		FB	2.0	345.8(353.8T)	012.9	AA 07000	
STAXX	STAXX	HELER	030		TF		FB	1.0	345.8(353.8T)	006.0	AA 07000	
VIGIL	VIGIL	VIGIL	010		IF		FB					
VIGIL	VIGIL	REDHI	020	IAF	TF		FB	2.0	035.7(043.7T)	021.6	AA 07900	
VIGIL	VIGIL	HELER	030		TF		FB	1.0	345.8(353.8T)	006.0	AA 07000	
		HELER	010	FACF	IF		FB				AA 07000	
		JIKTA	020	FAF	TF		FB	0.5	260.4(268.4T)	006.2	AA 06600	
		RW26L	030	MAP	TF		FB	0.3	260.4(268.4T)	005.9	AT 04710	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		260.4(268.4T)		AA 04849	
	MERTZ	050		DF		FO				AA 07000	
	MERTZ	060		HM	L	FO		290.0(298.0T)	007.0	AA 07000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	PUB	N381739.32	W1042546.01	N3817.655	W10425.767
	BONUH	N382337.55	W1041316.30	N3823.626	W10413.272
	DRAKE	N383624.05	W1042451.18	N3836.401	W10424.853
	HELER	N381737.43	W1041303.92	N3817.624	W10413.065
	JIKTA	N381727.14	W1042052.70	N3817.452	W10420.878
	MERTZ	N381701.63	W1043849.19	N3817.027	W10438.820
	ORWAY	N381632.08	W1040320.14	N3816.535	W10403.336
	REDHI	N381139.04	W1041214.76	N3811.651	W10412.246
	STAXX	N375848.29	W1041029.43	N3758.805	W10410.491
	VIGIL	N375603.37	W1043110.43	N3756.056	W10431.174
	RW26L	N381716.75	W1042824.66	N3817.279	W10428.411

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW26L	04649	62

CITY AND STATE <b>PUEBLO, CO</b>	ELEVATION: <b>4729</b>	THRE: <b>4649</b>	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: <b>PUEBLO MEMORIAL</b>		<b>RNAV</b>	<b>RNAV (GPS) RWY 26L, ORIG</b> 27 JUNE 2013	AMDT: <b>NONE</b>
	DATED:				