

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: HTL VOR/DME
LADIN INT	HTL VOR/DME	097.55 / 21.40	4000	CLIMB TO 2000 THEN CLIMBING LEFT TURN TO 3000 DIRECT HTL VOR/DME AND HOLD.
BANJO INT	HTL VOR/DME	310.13 / 25.78	3100	
				ADDITIONAL FLIGHT DATA: HOLD W, LT, 102.79 INBOUND. CHART FAS OBST: 1289 TREE 442211N/0844038W 1539 AAO 442112N/0844954W. DICAM TO RW09: 3.03/32. CHART MAXIMUM 6000 AT HTL VOR/DME. FAC CROSSES RWY C/L EXTENDED 3009 FROM THLD.

1. PT R SIDE OF COURSE 282.79 OUTBOUND 2800 FT WITHIN 10 MILES OF HTL VOR/DME (IAF)

2.

3. FAC 102.79 FAF _____ DIST FAF TO MAP _____ THLD _____4. MIN. ALT DICAM/HTL 2.50 DME 1840*

8. MSA FROM: HOUGHTON LAKE VOR/DME 3300

MAG VAR: 5W

EPOCH YEAR: 1985

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-9	1840	1	692	1840	1	692	1840	2	692	1840	2	692			
CIRCLING	1840	1	690	1840	1	690	1840	2	690	1840	2 1/4	690			
DICAM FIX MINIMUMS (DME REQUIRED)															
S-9	1540	1	392	1540	1	392	1540	1 1/4	392	1540	1 1/4	392			
CIRCLING	1600	1	450	1600	1	450	1600	1 1/2	450	1700	2	550			

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GAYLORD ALTIMETER SETTING AND INCREASE (SEE FORM 8260-10)

@ CAT D 800-2 1/4

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
4
CHECK

CITY AND STATE HOUGHTON LAKE, MI	ELEVATION: 1150 AIRPORT NAME: ROSCOMMON COUNTY - BLODGETT MEMORIAL	THRE: 1148 FACILITY IDENTIFIER: HTL	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 9, AMDT 5 7 MARCH 2013	SUP
				AMDT 4
				DATE 10/25/2007

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

ALL MDA 120 FT. INCREASE S-9 CAT B AND CIRCLING CAT D VISIBILITY 1/4, INCREASE CAT C AND CIRCLING CAT C 1/2. DICAM FIX MINIMUMS WHEN USING GAYLORD ALTIMETER SETTING, INCREASE CAT C 1/8.

CHART NOTE: CAT D STRAIGHT-IN MINIMUMS NA WHEN USING GAYLORD ALTIMETER SETTING.

*1960 WHEN USING GAYLORD ALTIMETER SETTING.

CITY AND STATE
HOUGHTON LAKE, MI

ELEVATION: 1150 THRE: 1148
AIRPORT NAME:
ROSCOMMON COUNTY - BLODGETT MEMORIAL

FACILITY
IDENTIFIER:
HTL

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
VOR RWY 9, AMDT 5
7 MARCH 2013

SUP:
AMDT: 4
DATED: 10/25/2007