

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	RNP: DA	
LAURI (IF)	JALDO (TF)(FB)(RNP 1.00)	178.01 / 6.10	2000	CLIMB TO 5000 ON TRACK 178.01 TO CEDEN AND ON TRACK 135.26 TO KEEZE AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 331.00 INBOUND. CHART FAS OBST: 336 LIGHT POLE 350400N/0895808W CHART LOC RWY 18R. DISTANCE TO THLD FROM 365 HATH: 0.98 NM ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S #TCH 324.3 MSL (DO NOT CHART)	
JALDO (FAF)	RW18C (MAP)(TF)(FO)	178.01 / 5.19			
RW18C (MAP)	CEDEN (TF)(FB)(RNP 1.00)	178.01 / 6.95			
CEDEN	KEEZE (TF)(FO)(RNP 1.00)	135.26 / 6.41	5000		
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT LAURI 3. FAC: 178.01 FAF: JALDO DIST FAF TO MAP: <u> </u> THLD: <u> </u> 4. MIN. ALT: LAURI 3900, JALDO 2000 5. DIST TO THLD FROM OM: <u>5.19</u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>2000</u> GS ALT AT: JALDO 2000 OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: 53.7# 34:1 IS CLEAR 8. MSA FROM: RW18C 2600				MAG VAR: 1E EPOCH YEAR: 2000	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: NA		
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
AUTHORIZATION REQUIRED					
RNP 0.30 DA*	636	3500	365	636	3500
RNP 0.30 DA	728	5400	457	728	5400
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -10C (14F) OR ABOVE 54C (130F). CHART NOTE: *MISSED APPROACH REQUIRES A MINIMUM CLIMB OF 400 FEET PER NM TO 1000. CHART NOTE: GPS REQUIRED. (SEE FORM 8260-10)					
CITY AND STATE		ELEVATION: 341 THRE: 271		FACILITY IDENTIFIER: RNAV	
MEMPHIS, TN		AIRPORT NAME: MEMPHIS INTL		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Y RWY 18C, ORIG-C 27 JUNE 2013	
				SUP: AMDT: ORIG-B DATED 05/31/2012	

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: RADAR REQUIRED.

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE RNP 0.30* ALL CATS VISIBILITY TO RVR 6000 AND RNP 0.30 ALL CATS VISIBILITY TO 1 1/2 MILES.

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 18R.

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

CITY AND STATE

MEMPHIS, TN

ELEVATION: 341

THRE: 271

AIRPORT NAME:

MEMPHIS INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (RNP) Y RWY 18C, ORIG-C

27 JUNE 2013

SUP:

AMDT: ORIG-B

DATED: 05/31/2012

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KMEMK7FH18CY	H	010LAURIK7EA0E	I	1F			+ 039C0	18000			A	FS
SUSAP	KMEMK7FH18CY	H	020JALDOK7EA1E	F	010TF			+ 020C0			RW18C	K7PGA	FS
SUSAP	KMEMK7FH18CY	H	020JALDOK7EA2W						A031				FS
SUSAP	KMEMK7FH18CY	H	030RW18CK7PG0GY	M	031TF			00324		-300		A	FS
SUSAP	KMEMK7FH18CY	H	040CEDENK7EA0E	M	010TF							A	FS
SUSAP	KMEMK7FH18CY	H	050KEEZ EK7EA0EY		010TF			+ 050C0				A	FS
SUSAP	KMEMK7FH18CY	H	060KEEZ EK7EA0EE	R	HM	33100050		+ 050C0				A	FS

[illegible][illegible]Page 3 of 4 Pages

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (RNP)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		LAURI	010	FACF	IF		FB				AA 03900	
		JALDO	020	FAF	TF		FB	1.0			AA 02000	
		RW18C	030	MAP	TF		FO	0.3			AT 00324	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	CEDEN	040		TF		FB	1.0				
	KEEZE	050		TF		FO	1.0			AA 05000	
	KEEZE	060		HM	R	FO		331.0(332.0T)	005.0	AA 05000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CEDEN	N345618.93	W0895825.45	N3456.316	W08958.424
	JALDO	N350828.22	W0895840.77	N3508.470	W08958.680
	KEEZE	N345140.42	W0895302.25	N3451.674	W08953.038
	LAURI	N351434.92	W0895848.50	N3514.582	W08958.808
	RW18C	N350316.54	W0895834.21	N3503.276	W08958.570

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18C	00271	54

CITY AND STATE
MEMPHIS, TN

ELEVATION: 341 THRE: 271
 AIRPORT NAME:
 MEMPHIS INTL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
 RNAV (RNP) Y RWY 18C, ORIG-C
 27 JUNE 2013

SUP:	
AMDT:	ORIG-B
DATED:	05/31/2012