

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CLEBURNE, TX	CLEBURNE RGNL	27 JUNE 2013	ORIG-A

TAKEOFF MINIMUMS:

RWY 15, STANDARD
RWY 33, 300 – 1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 422 FT PER NM TO 1200.

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 15, MULTIPLE POLES, BEGINNING 952 FT FROM DER, 425 FT RIGHT OF CENTERLINE, UP TO 30 FT AGL/ 883 FT MSL. TREE, 441 FT FROM DER, 501 FT RIGHT OF CENTERLINE, 55 FT AGL/868 FT MSL. POLE, 1137 FT FROM DER, 742 FT LEFT OF CENTERLINE 35 FT AGL/ 875 FT MSL.

NOTE: RWY 33, MULTIPLE TREES, BEGINNING 602 FT FROM DER, 300 FT LEFT OF CENTERLINE, UP TO 55 FT AGL/873 FT MSL. WELL DRILLING RIG, 3268 FT FROM DER, 123 FT LEFT OF CENTERLINE, 174 FT AGL/1043 FT MSL. WELL DRILLING RIG, 1.2 NM FROM DER, 615 FT LEFT OF CENTERLINE, 104 FT AGL/976 FT MSL. TRANSMISSION POLE, 1817 FT FROM DER, 183 FT LEFT OF CENTERLINE, 80 FT AGL/ 900 FT MSL.

CONTROLLING OBSTACLES:

RWY 33 – 976 FT MSL WELL DRILLING RIG 322211.95N/0972629.30W - 1043 FT MSL WELL DRILLING RIG 322243.27N/0972649.63W

